

PART A INVITATION TO BID

VOLLARE HEE		INVITA	ATION	TO BID				
YOU ARE HEREE	BY INVITED TO BID	FOR REQUIREMENTS	OF TH	E (NAME OF DE	PAR	TMENT/ PUBLIC E	ENTITY)	
BID NUMBER:	SCM03-19/20-0268 NMA	CLOSING DATE:		09/10/2019		OSING TIME.	441100	
DESCRIPTION	DEPARTMENT of H	RY,COMMISSION OF HANY OTHER FACILITY EALTH FOR A PERIOD	OF 36	QUIRING THE	SAM	E SERVICE IN	THE EASTE	RN CAPE
SCM UNIT - LEVI	EL 2	ENTS MAY BE DEPOSIT	ED IN	THE BID BOX S	SITUA	ATED AT (STREET	(ADDRESS)	
NELSON MANDE	LA ACADEMIC HO	SPITAL		1				
SISSONS STREET								
MTHATHA, 5100								
BIDDING PROCEI	DURE ENQUIRIES I	MAY BE DIRECTED TO	TE	CHNICAL ENQU	JIRIE	S MAY BE DIREC	TED TO:	
CONTACT PERSO	N MS N. MFEN	BUZA	CO PE	NTACT RSON	MS	N. MFENGUZA		
TELEPHONE NUMBER	047 502 4518	0		LEPHONE MBER	04	7 502 4518/047 50	2	
E-MAIL ADDRESS	nobuntu.mfer	nguza@echealth.gov.za		AIL ADDRESS	no	buntu.mfenguza@	echealth.go	v.za
		SUPPLIEF	RINFO	RMATION				
NAME OF BIDDER	2							
POSTAL ADDRES	s							
STREET ADDRES	S							
TELEPHONE NUMBER	CODE			NUMBER				
CELLPHONE NUMBER								
FACSIMILE NUMBER	CODE			NUMBER				
E-MAIL ADDRESS								
VAT REGISTRATIONUMBER								
SUPPLIER COMPLIANCE STATUS	TAX COMPLIANCE SYSTEM PIN:		OR	CENTRAL SUPPLIER DATABASE No:	MAA			
B-BBEE STATUS	TICK AF	PPLICABLE BOX]	B-BI	BEE STATUS	MAA		PLICABLE BO)Y1
LEVEL VERIFICATION			LEV	EL SWORN		200		3. 4. 8
CERTIFICATE	Yes	☐ No	AFF	IDAVIT		Yes		٧o
[A B-BBEE STATU	IS LEVEL VERIFICA ORDE	ATION CERTIFICATE/ S R TO QUALIFY FOR PR	WORN EFERI	I AFFIDAVIT (FO	OR EI	 MES & QSEs) MUS B-RREF1	ST BE SUBM	ITTED IN
ARE YOU THE ACCREDITED REPRESENTATIVE IN SOUTH AFRICA FOR THE GOODS /SERVICES /WORK OFFERED?	∃Yes	□No	ARE BAS THE /SEF	YOU A FOREIG ED SUPPLIER F GOODS RVICES /WORKS ERED?	€N FOR	☐Yes [IF YES, ANSWE QUESTIONNAIR		□No
			1		CICNIA	TURE A		
		DRAFT	ED BY:		U	10/6	DATE COR	18
		RECOM	IMENDED	BY	4		100/09	119

REVIEWED BY:

SCMU3-19/20-0268-NMA

APPROVED BY BSC CHAIRPERSON

ADVERT APPROVED BY:

THE ENTITY A RESIDENT OF THE REPUBLIC OF SOUTH AFRICA (RSA)? DES THE ENTITY HAVE A BRANCH IN THE RSA? DES THE ENTITY HAVE A PERMANENT ESTABLISHMENT IN THE RSA? DES THE ENTITY HAVE ANY SOURCE OF INCOME IN THE RSA? THE ENTITY LIABLE IN THE RSA FOR ANY FORM OF TAXATION? THE ANSWER IS "NO" TO ALL OF THE ABOVE, THEN IT IS NOT A REQUIREMENT TO REGISTE ATUS SYSTEM PIN CODE FROM THE SOUTH AFRICAN REVENUE SERVICE (SARS) AND IF TERMS AND CONDITIONS FOR BIDDING BID SUBMISSION: BIDS MUST BE DELIVERED BY THE STIPULATED TIME TO THE CORRECT ADDRESS. LATE BID ACCEPTED FOR CONSIDERATION. ALL BIDS MUST BE SUBMITTED ON THE OFFICIAL FORMS PROVIDED—(NOT TO BE RE-TYPED PRESCRIBED IN THE BID DOCUMENT. THIS BID IS SUBJECT TO THE PREFERENTIAL PROCUREMENT POLICY FRAMEWORK ACT, 200 PREFERENTIAL PROCUREMENT POLICY FRAMEWORK ACT,	S WILL NOT BE O AND THE MANNER O AND THE ACT (GCC) AND, IF
DES THE ENTITY HAVE A PERMANENT ESTABLISHMENT IN THE RSA? THE ENTITY HAVE ANY SOURCE OF INCOME IN THE RSA? THE ENTITY LIABLE IN THE RSA FOR ANY FORM OF TAXATION? THE ANSWER IS "NO" TO ALL OF THE ABOVE, THEN IT IS NOT A REQUIREMENT TO REGISTE ATUS SYSTEM PIN CODE FROM THE SOUTH AFRICAN REVENUE SERVICE (SARS) AND IF PART B TERMS AND CONDITIONS FOR BIDDING BID SUBMISSION: BIDS MUST BE DELIVERED BY THE STIPULATED TIME TO THE CORRECT ADDRESS. LATE BID ACCEPTED FOR CONSIDERATION. ALL BIDS MUST BE SUBMITTED ON THE OFFICIAL FORMS PROVIDED—(NOT TO BE RE-TYPED PRESCRIBED IN THE BID DOCUMENT. THIS BID IS SUBJECT TO THE PREFERENTIAL PROCUREMENT POLICY FRAMEWORK ACT, 200 PREFERENTIAL PROCUREMENT REGULATIONS, 2017, THE GENERAL CONDITIONS OF CONTRACT. THE SUCCESSFUL BIDDER WILL BE REQUIRED TO FILL IN AND SIGN A WRITTEN CONTRACT AX COMPLIANCE REQUIREMENTS BIDDERS MUST ENSURE COMPLIANCE WITH THEIR TAX OBLIGATIONS. BIDDERS ARE REQUIRED TO SUBMIT THEIR UNIQUE PERSONAL IDENTIFICATION NUMBER (PICTO ENABLE) THE ORGAN OF STATE TO VERIFY THE TAXPAYER'S PROFILE AND TAX STATUS. APPLICATION FOR TAX COMPLIANCE STATUS (TCS) PIN MAY BE MADE VIA E-FILING THROUGHWW.SARS.GOV.ZA.	YES N YES N YES YES FOR A TAX COMPLIA NOT REGISTER AS PE S WILL NOT BE O AND THE MANNER O AND THE
DES THE ENTITY HAVE ANY SOURCE OF INCOME IN THE RSA? THE ENTITY LIABLE IN THE RSA FOR ANY FORM OF TAXATION? THE ANSWER IS "NO" TO ALL OF THE ABOVE, THEN IT IS NOT A REQUIREMENT TO REGISTE ATUS SYSTEM PIN CODE FROM THE SOUTH AFRICAN REVENUE SERVICE (SARS) AND IF ELOW. PART B TERMS AND CONDITIONS FOR BIDDING BIDS MUST BE DELIVERED BY THE STIPULATED TIME TO THE CORRECT ADDRESS. LATE BID ACCEPTED FOR CONSIDERATION. ALL BIDS MUST BE SUBMITTED ON THE OFFICIAL FORMS PROVIDED—(NOT TO BE RE-TYPED PRESCRIBED IN THE BID DOCUMENT. THIS BID IS SUBJECT TO THE PREFERENTIAL PROCUREMENT POLICY FRAMEWORK ACT, 200 PREFERENTIAL PROCUREMENT REGULATIONS, 2017, THE GENERAL CONDITIONS OF CONTRACT. THE SUCCESSFUL BIDDER WILL BE REQUIRED TO FILL IN AND SIGN A WRITTEN CONTRACT AX COMPLIANCE REQUIREMENTS BIDDERS MUST ENSURE COMPLIANCE WITH THEIR TAX OBLIGATIONS. BIDDERS ARE REQUIRED TO SUBMIT THEIR UNIQUE PERSONAL IDENTIFICATION NUMBER (PICE NAME) OF CONTRACT THE ORGAN OF STATE TO VERIFY THE TAXPAYER'S PROFILE AND TAX STATUS. APPLICATION FOR TAX COMPLIANCE STATUS (TCS) PIN MAY BE MADE VIA E-FILING THROUGH WWW.SARS.GOV.ZA.	YES N YES YES R FOR A TAX COMPLIA NOT REGISTER AS PE
THE ENTITY LIABLE IN THE RSA FOR ANY FORM OF TAXATION? THE ANSWER IS "NO" TO ALL OF THE ABOVE, THEN IT IS NOT A REQUIREMENT TO REGISTE TATUS SYSTEM PIN CODE FROM THE SOUTH AFRICAN REVENUE SERVICE (SARS) AND IF SHOW. PART B TERMS AND CONDITIONS FOR BIDDING BIDS MUST BE DELIVERED BY THE STIPULATED TIME TO THE CORRECT ADDRESS. LATE BID ACCEPTED FOR CONSIDERATION. ALL BIDS MUST BE SUBMITTED ON THE OFFICIAL FORMS PROVIDED—(NOT TO BE RE-TYPED PRESCRIBED IN THE BID DOCUMENT. THIS BID IS SUBJECT TO THE PREFERENTIAL PROCUREMENT POLICY FRAMEWORK ACT, 200 PREFERENTIAL PROCUREMENT REGULATIONS, 2017, THE GENERAL CONDITIONS OF CONTRACT. THE SUCCESSFUL BIDDER WILL BE REQUIRED TO FILL IN AND SIGN A WRITTEN CONTRACT AX COMPLIANCE REQUIREMENTS BIDDERS MUST ENSURE COMPLIANCE WITH THEIR TAX OBLIGATIONS. BIDDERS ARE REQUIRED TO SUBMIT THEIR UNIQUE PERSONAL IDENTIFICATION NUMBER (PI O ENABLE THE ORGAN OF STATE TO VERIFY THE TAXPAYER'S PROFILE AND TAX STATUS. APPLICATION FOR TAX COMPLIANCE STATUS (TCS) PIN MAY BE MADE VIA E-FILING THROUGH WWW.SARS.GOV.ZA. BIDDERS MAY ALSO SUBMIT A PRINTED TCS CERTIFICATE TOGETHER WITH THE BID.	YES RER FOR A TAX COMPLIA NOT REGISTER AS PE S WILL NOT BE O AND THE MANNER O AND THE ACT (GCC) AND, IF
THE ENTITY LIABLE IN THE RSA FOR ANY FORM OF TAXATION? THE ANSWER IS "NO" TO ALL OF THE ABOVE, THEN IT IS NOT A REQUIREMENT TO REGISTE TATUS SYSTEM PIN CODE FROM THE SOUTH AFRICAN REVENUE SERVICE (SARS) AND IF SHOW. PART B TERMS AND CONDITIONS FOR BIDDING BIDS MUST BE DELIVERED BY THE STIPULATED TIME TO THE CORRECT ADDRESS. LATE BID ACCEPTED FOR CONSIDERATION. ALL BIDS MUST BE SUBMITTED ON THE OFFICIAL FORMS PROVIDED—(NOT TO BE RE-TYPED PRESCRIBED IN THE BID DOCUMENT. THIS BID IS SUBJECT TO THE PREFERENTIAL PROCUREMENT POLICY FRAMEWORK ACT, 200 PREFERENTIAL PROCUREMENT REGULATIONS, 2017, THE GENERAL CONDITIONS OF CONTRACT. THE SUCCESSFUL BIDDER WILL BE REQUIRED TO FILL IN AND SIGN A WRITTEN CONTRACT AX COMPLIANCE REQUIREMENTS BIDDERS MUST ENSURE COMPLIANCE WITH THEIR TAX OBLIGATIONS. BIDDERS ARE REQUIRED TO SUBMIT THEIR UNIQUE PERSONAL IDENTIFICATION NUMBER (PI O ENABLE THE ORGAN OF STATE TO VERIFY THE TAXPAYER'S PROFILE AND TAX STATUS. APPLICATION FOR TAX COMPLIANCE STATUS (TCS) PIN MAY BE MADE VIA E-FILING THROUGH WWW.SARS.GOV.ZA. BIDDERS MAY ALSO SUBMIT A PRINTED TCS CERTIFICATE TOGETHER WITH THE BID.	YES RER FOR A TAX COMPLIA NOT REGISTER AS PE S WILL NOT BE O AND THE MANNER O AND THE ACT (GCC) AND, IF
THE ANSWER IS "NO" TO ALL OF THE ABOVE, THEN IT IS NOT A REQUIREMENT TO REGISTE ATUS SYSTEM PIN CODE FROM THE SOUTH AFRICAN REVENUE SERVICE (SARS) AND IF SLOW. PART B TERMS AND CONDITIONS FOR BIDDING BIDS MUST BE DELIVERED BY THE STIPULATED TIME TO THE CORRECT ADDRESS. LATE BID ACCEPTED FOR CONSIDERATION. ALL BIDS MUST BE SUBMITTED ON THE OFFICIAL FORMS PROVIDED—(NOT TO BE RE-TYPED PRESCRIBED IN THE BID DOCUMENT. THIS BID IS SUBJECT TO THE PREFERENTIAL PROCUREMENT POLICY FRAMEWORK ACT, 200 PREFERENTIAL PROCUREMENT REGULATIONS, 2017, THE GENERAL CONDITIONS OF CONTRACT. THE SUCCESSFUL BIDDER WILL BE REQUIRED TO FILL IN AND SIGN A WRITTEN CONTRACT AX COMPLIANCE REQUIREMENTS BIDDERS MUST ENSURE COMPLIANCE WITH THEIR TAX OBLIGATIONS. BIDDERS ARE REQUIRED TO SUBMIT THEIR UNIQUE PERSONAL IDENTIFICATION NUMBER (PI O ENABLE THE ORGAN OF STATE TO VERIFY THE TAXPAYER'S PROFILE AND TAX STATUS. PPLICATION FOR TAX COMPLIANCE STATUS (TCS) PIN MAY BE MADE VIA E-FILING THROUGH WWW.SARS.GOV.ZA.	S WILL NOT BE O AND THE MANNER O AND THE MACT (GCC) AND, IF
PART B TERMS AND CONDITIONS FOR BIDDING BID SUBMISSION: BIDS MUST BE DELIVERED BY THE STIPULATED TIME TO THE CORRECT ADDRESS. LATE BID ACCEPTED FOR CONSIDERATION. ALL BIDS MUST BE SUBMITTED ON THE OFFICIAL FORMS PROVIDED—(NOT TO BE RE-TYPED PRESCRIBED IN THE BID DOCUMENT. THIS BID IS SUBJECT TO THE PREFERENTIAL PROCUREMENT POLICY FRAMEWORK ACT, 200 PREFERENTIAL PROCUREMENT REGULATIONS, 2017, THE GENERAL CONDITIONS OF CONTRACT. THE SUCCESSFUL BIDDER WILL BE REQUIRED TO FILL IN AND SIGN A WRITTEN CONTRACT AX COMPLIANCE REQUIREMENTS BIDDERS MUST ENSURE COMPLIANCE WITH THEIR TAX OBLIGATIONS. BIDDERS ARE REQUIRED TO SUBMIT THEIR UNIQUE PERSONAL IDENTIFICATION NUMBER (PION ENABLE) THE ORGAN OF STATE TO VERIFY THE TAXPAYER'S PROFILE AND TAX STATUS. PEPPLICATION FOR TAX COMPLIANCE STATUS (TCS) PIN MAY BE MADE VIA E-FILING THROUGH WWW.SARS.GOV.ZA.	S WILL NOT BE O AND THE MANNER O AND THE ACT (GCC) AND, IF
TERMS AND CONDITIONS FOR BIDDING BIDS SUBMISSION: BIDS MUST BE DELIVERED BY THE STIPULATED TIME TO THE CORRECT ADDRESS. LATE BID ACCEPTED FOR CONSIDERATION. ALL BIDS MUST BE SUBMITTED ON THE OFFICIAL FORMS PROVIDED—(NOT TO BE RE-TYPED PRESCRIBED IN THE BID DOCUMENT. THIS BID IS SUBJECT TO THE PREFERENTIAL PROCUREMENT POLICY FRAMEWORK ACT, 200 PREFERENTIAL PROCUREMENT REGULATIONS, 2017, THE GENERAL CONDITIONS OF CONTRACT. THE SUCCESSFUL BIDDER WILL BE REQUIRED TO FILL IN AND SIGN A WRITTEN CONTRACT AX COMPLIANCE REQUIREMENTS BIDDERS MUST ENSURE COMPLIANCE WITH THEIR TAX OBLIGATIONS. BIDDERS ARE REQUIRED TO SUBMIT THEIR UNIQUE PERSONAL IDENTIFICATION NUMBER (PI O ENABLE THE ORGAN OF STATE TO VERIFY THE TAXPAYER'S PROFILE AND TAX STATUS. APPLICATION FOR TAX COMPLIANCE STATUS (TCS) PIN MAY BE MADE VIA E-FILING THROUGH WWW.SARS.GOV.ZA. BIDDERS MAY ALSO SUBMIT A PRINTED TCS CERTIFICATE TOGETHER WITH THE RID.	O AND THE ACT (GCC) AND, IF
TERMS AND CONDITIONS FOR BIDDING BIDS SUBMISSION: BIDS MUST BE DELIVERED BY THE STIPULATED TIME TO THE CORRECT ADDRESS. LATE BID ACCEPTED FOR CONSIDERATION. ALL BIDS MUST BE SUBMITTED ON THE OFFICIAL FORMS PROVIDED—(NOT TO BE RE-TYPED PRESCRIBED IN THE BID DOCUMENT. THIS BID IS SUBJECT TO THE PREFERENTIAL PROCUREMENT POLICY FRAMEWORK ACT, 200 PREFERENTIAL PROCUREMENT REGULATIONS, 2017, THE GENERAL CONDITIONS OF CONTRACT. THE SUCCESSFUL BIDDER WILL BE REQUIRED TO FILL IN AND SIGN A WRITTEN CONTRACT AX COMPLIANCE REQUIREMENTS BIDDERS MUST ENSURE COMPLIANCE WITH THEIR TAX OBLIGATIONS. BIDDERS ARE REQUIRED TO SUBMIT THEIR UNIQUE PERSONAL IDENTIFICATION NUMBER (PI O ENABLE THE ORGAN OF STATE TO VERIFY THE TAXPAYER'S PROFILE AND TAX STATUS. APPLICATION FOR TAX COMPLIANCE STATUS (TCS) PIN MAY BE MADE VIA E-FILING THROUGH WWW.SARS.GOV.ZA. BIDDERS MAY ALSO SUBMIT A PRINTED TCS CERTIFICATE TOGETHER WITH THE RID.	O AND THE ACT (GCC) AND, IF
BIDS MUST BE DELIVERED BY THE STIPULATED TIME TO THE CORRECT ADDRESS. LATE BID ACCEPTED FOR CONSIDERATION. ALL BIDS MUST BE SUBMITTED ON THE OFFICIAL FORMS PROVIDED—(NOT TO BE RE-TYPED PRESCRIBED IN THE BID DOCUMENT. THIS BID IS SUBJECT TO THE PREFERENTIAL PROCUREMENT POLICY FRAMEWORK ACT, 200 PREFERENTIAL PROCUREMENT REGULATIONS, 2017, THE GENERAL CONDITIONS OF CONTRACT. THE SUCCESSFUL BIDDER WILL BE REQUIRED TO FILL IN AND SIGN A WRITTEN CONTRACT AX COMPLIANCE REQUIREMENTS BIDDERS MUST ENSURE COMPLIANCE WITH THEIR TAX OBLIGATIONS. BIDDERS ARE REQUIRED TO SUBMIT THEIR UNIQUE PERSONAL IDENTIFICATION NUMBER (PICE OF ENABLE) THE ORGAN OF STATE TO VERIFY THE TAXPAYER'S PROFILE AND TAX STATUS. APPLICATION FOR TAX COMPLIANCE STATUS (TCS) PIN MAY BE MADE VIA E-FILING THROUGH WWW.SARS.GOV.ZA. BIDDERS MAY ALSO SUBMIT A PRINTED TCS CERTIFICATE TOGETHER WITH THE BID.	O AND THE ACT (GCC) AND, IF
ALL BIDS MUST BE SUBMITTED ON THE OFFICIAL FORMS PROVIDED—(NOT TO BE RE-TYPED PRESCRIBED IN THE BID DOCUMENT. THIS BID IS SUBJECT TO THE PREFERENTIAL PROCUREMENT POLICY FRAMEWORK ACT, 200 PREFERENTIAL PROCUREMENT REGULATIONS, 2017, THE GENERAL CONDITIONS OF CONTRACT. APPLICABLE, ANY OTHER SPECIAL CONDITIONS OF CONTRACT. THE SUCCESSFUL BIDDER WILL BE REQUIRED TO FILL IN AND SIGN A WRITTEN CONTRACT. BIDDERS MUST ENSURE COMPLIANCE WITH THEIR TAX OBLIGATIONS. BIDDERS ARE REQUIRED TO SUBMIT THEIR UNIQUE PERSONAL IDENTIFICATION NUMBER (PICTO ENABLE THE ORGAN OF STATE TO VERIFY THE TAXPAYER'S PROFILE AND TAX STATUS. APPLICATION FOR TAX COMPLIANCE STATUS (TCS) PIN MAY BE MADE VIA E-FILING THROUGHWW.SARS.GOV.ZA. BIDDERS MAY ALSO SUBMIT A PRINTED TCS CERTIFICATE TOGETHER WITH THE BID.	O AND THE ACT (GCC) AND, IF
THIS BID IS SUBJECT TO THE PREFERENTIAL PROCUREMENT POLICY FRAMEWORK ACT, 200 PREFERENTIAL PROCUREMENT REGULATIONS, 2017, THE GENERAL CONDITIONS OF CONTRAPPLICABLE, ANY OTHER SPECIAL CONDITIONS OF CONTRACT. THE SUCCESSFUL BIDDER WILL BE REQUIRED TO FILL IN AND SIGN A WRITTEN CONTRACT AX COMPLIANCE REQUIREMENTS BIDDERS MUST ENSURE COMPLIANCE WITH THEIR TAX OBLIGATIONS. BIDDERS ARE REQUIRED TO SUBMIT THEIR UNIQUE PERSONAL IDENTIFICATION NUMBER (PICTOR ENABLE) THE ORGAN OF STATE TO VERIFY THE TAXPAYER'S PROFILE AND TAX STATUS. APPLICATION FOR TAX COMPLIANCE STATUS (TCS) PIN MAY BE MADE VIA E-FILING THROUGHWW.SARS.GOV.ZA.	0 AND THE ACT (GCC) AND, IF
APPLICABLE, ANY OTHER SPECIAL CONDITIONS OF CONTRACT. THE SUCCESSFUL BIDDER WILL BE REQUIRED TO FILL IN AND SIGN A WRITTEN CONTRACT AX COMPLIANCE REQUIREMENTS BIDDERS MUST ENSURE COMPLIANCE WITH THEIR TAX OBLIGATIONS. BIDDERS ARE REQUIRED TO SUBMIT THEIR UNIQUE PERSONAL IDENTIFICATION NUMBER (PICTO ENABLE THE ORGAN OF STATE TO VERIFY THE TAXPAYER'S PROFILE AND TAX STATUS. APPLICATION FOR TAX COMPLIANCE STATUS (TCS) PIN MAY BE MADE VIA E-FILING THROUGHWW.SARS.GOV.ZA. BIDDERS MAY ALSO SUBMIT A PRINTED TCS CERTIFICATE TOGETHER WITH THE RID.	ACT (GCC) AND, IF
AX COMPLIANCE REQUIREMENTS BIDDERS MUST ENSURE COMPLIANCE WITH THEIR TAX OBLIGATIONS. BIDDERS ARE REQUIRED TO SUBMIT THEIR UNIQUE PERSONAL IDENTIFICATION NUMBER (PICTO ENABLE THE ORGAN OF STATE TO VERIFY THE TAXPAYER'S PROFILE AND TAX STATUS. APPLICATION FOR TAX COMPLIANCE STATUS (TCS) PIN MAY BE MADE VIA E-FILING THROUGHWW.SARS.GOV.ZA. BIDDERS MAY ALSO SUBMIT A PRINTED TCS CERTIFICATE TOGETHER WITH THE RID	FORM (SBD7).
AX COMPLIANCE REQUIREMENTS BIDDERS MUST ENSURE COMPLIANCE WITH THEIR TAX OBLIGATIONS. BIDDERS ARE REQUIRED TO SUBMIT THEIR UNIQUE PERSONAL IDENTIFICATION NUMBER (PICTOR ENABLE THE ORGAN OF STATE TO VERIFY THE TAXPAYER'S PROFILE AND TAX STATUS. APPLICATION FOR TAX COMPLIANCE STATUS (TCS) PIN MAY BE MADE VIA E-FILING THROUGHWW.SARS.GOV.ZA. BIDDERS MAY ALSO SUBMIT A PRINTED TCS CERTIFICATE TOGETHER WITH THE RID.	
BIDDERS MUST ENSURE COMPLIANCE WITH THEIR TAX OBLIGATIONS. BIDDERS ARE REQUIRED TO SUBMIT THEIR UNIQUE PERSONAL IDENTIFICATION NUMBER (PICTO ENABLE THE ORGAN OF STATE TO VERIFY THE TAXPAYER'S PROFILE AND TAX STATUS. SPPLICATION FOR TAX COMPLIANCE STATUS (TCS) PIN MAY BE MADE VIA E-FILING THROUGHWW.SARS.GOV.ZA. BIDDERS MAY ALSO SUBMIT A PRINTED TCS CERTIFICATE TOGETHER WITH THE RID.	
APPLICATION FOR TAX COMPLIANCE STATUS (TCS) PIN MAY BE MADE VIA E-FILING THROUGH WWW.SARS.GOV.ZA.	
PPLICATION FOR TAX COMPLIANCE STATUS (TCS) PIN MAY BE MADE VIA E-FILING THROUGH WWW.SARS.GOV.ZA. IIDDERS MAY ALSO SUBMIT A PRINTED TCS CERTIFICATE TOGETHER WITH THE BID.	
IDDERS MAY ALSO SUBMIT A PRINTED TCS CERTIFICATE TOGETHER WITH THE BID.	THE SARS WEBSITE
N BIDS WHERE CONSORTIA / JOINT VENTURES / SUB-CONTRACTORS ARE INVOLVED, EACH F SEPARATE TCS CERTIFICATE / PIN / CSD NUMBER.	PARTY MUST SUBMIT
/HERE NO TCS PIN IS AVAILABLE BUT THE BIDDER IS REGISTERED ON THE CENTRAL SUPPLI CSD), A CSD NUMBER MUST BE PROVIDED.	ER DATABASE
O BIDS WILL BE CONSIDERED FROM PERSONS IN THE SERVICE OF THE STATE, COMPANIES /HO ARE PERSONS IN THE SERVICE OF THE STATE, OR CLOSE CORPORATIONS WITH MEMBI HE SERVICE OF THE STATE."	WITH DIRECTORS ERS PERSONS IN
NB: FAILURE TO PROVIDE ANY OF THE ABOVE PARTICULARS MAY RENDER THE BID	INVALID.
SIGNATURE OF BIDDER:	
CAPACITY UNDER WHICH THIS BID IS SIGNED: (Proof of authority must be submitted e.g. company resolution)	
DATE:	

1. **TABLE OF CONTENTS**

Invitation to Bid (SBD 1)

Part 1 - Conditions of Bid

Part 2 - Conditions of Contract and Operational Requirements

Part 3 - Bid Strategy

Part 4 - Specifications

Part 5 - Bid Forms and related documentation

<u>Schedule A</u> – Government Procurement: General Conditions of Contract

Schedule B - CSD REGISTRATION FORMS

Schedule C - Pricing Schedule (SBD 3.1)

Schedule D - Declaration of Interest (SBD 4)

Schedule E -

Declaration of Bidder's Past SCM Practices (SBD8) Schedule F -Certificate of Bid Determination (SBD9)

Schedule G - Qualifications and experience

Schedule H - Organisation type

Schedule I - Organisational Structure

Schedule J - Details of Bidder's nearest office

Schedule K -Financial Particulars

Schedule L -Preference Points Claim Forms (SBD 6.1)

2. **DEFINITIONS**

The rules of interpretation and defined terms contained in the General Conditions of Contract (GCC) shall apply to this invitation to bid unless the context requires otherwise.

In addition the following terms used in this invitation to bid shall, unless indicated otherwise, have the meanings assigned to such terms in the table below.

ECDoH	means the Eastern Cape Department of Health acting for and on behalf of the Eastern Cape Provincial Government;
Invitation to bid	 means this invitation to bid comprising The cover page and the table of content and definitions Part 1 which details the Conditions of Bid; Part 2 which details the Conditions of Contract and Operational Requirements; Part 3 which details the bid strategy Part 4 which details the Terms of Reference relating to the Technology / Services Part 5 which contains all the requisite bid forms and certificates; As read with GCC-General Conditions of Contract
Goods	means the requirements defined on the cover page of this invitation to bid and described in detail in the Specifications;
Specifications	means the specifications contained in Part 4 of this invitation to bid;

PART 1 Conditions of Bid

1. BACKGROUND AND INTRODUCTORY PROVISIONS

The Department intends to engage suitably qualified suppliers to supply and deliver PHACO & VITRECTOMY MACHINE at Nelson Mandela Academic Hospital in Mthatha

2. OFFER AND SPECIAL CONDITIONS

- 2.1 Without detracting from the generality of clause 2.2 below, bidders must submit a completed and signed Invitation to Bid form (SBD 1) and requisite bid forms attached as Part 5) with their bids.
- 2.2 <u>All bids submitted in reply to this invitation to bid should incorporate all the forms, parts, certificates and other documentation forming part of this invitation to bid, duly completed where required.</u>
- 2.3 It is a requirement that CSD Registration forms be submitted with the bid. Failure to submit will invalidate your bid.
- 2.4 In the event that any form or certificate provided in Part 5 of this invitation to bid does not have adequate space for the bidder to provide the requested details, the bidder should attach an annexure to such form or certificate on which the requested details should be provided and the bidder should refer to such annexure in the form or certificate provided.

3. CLOSING TIME OF BIDS AND PROVISIONS RELATING TO SUBMISSION OF BIDS

- 3.1 The closing time for the receipt of bids in response to this invitation to bid is detailed on the cover page of this invitation to bid.
- 3.2 All bids must be submitted in a sealed envelope bearing the bid number, bid description and closing date.
- 3.4 All bids must be received before the closing time and date stipulated above and must be posted to or deposited in the bid box at the address detailed on the cover page of this invitation to bid.

4. ENQUIRIES

Should any bidder have any enquiries relating to this invitation to bid, such inquiries may only be addressed to the person/s detailed on the cover page to this invitation to bid at the number/s stipulated.

NO BRIEFING OR SITE INSPECTION WILL BE REQUIRED

6. CSD REGISTRATION

It is a requirement that bidders register on the Central Supplier Database and submit proof of registration with the bid. Failure to register may invalidate your bid. Tax Clearance Compliance Verification will be done with the CSD and SARS.

DRAFTED BY:	SIGNATURE	DATE
RECOMMENDED BY	eray co	12/05/
REVIEWED BY:	11/01	120 9 4
APPROVED BY BSC CHAIRPERSON	Au Tulos)	12/09/20
ADVERT APPROVED BY:	1 Coco	12/09/16
U3-19/20-0268-NMA	THE STATE OF THE S	12 39 di

7. CONTRACT PRICING AND ADJUSTMENTS

- 7.1 The bidder must complete in FULL price details for the Goods and or Services on the Pricing Schedule form/s attached_which completed form/s must be submitted together with the bid documents. Failure to comply with this requirement may invalidate the bid.
- 7.2 Prices quoted must be furnished on the basis of supply, delivery, installation, commissioning and maintenance, including warranty.
- 7.3 Bid pricing details must be completed manually using clear BLACK INK and duly signed. Where electronically completed submissions are made, every page must be initialed.
- 7.4 All bid prices must be inclusive of 15% Value-Added Tax.
- 7.5 It is an express requirement of this invitation to bid that the bidders provide some transparency in respect to their pricing approach. In this regard, bidders must indicate the basis on which they have calculated their pricing by completing all aspects of the Pricing Schedule
- 7.6 The prices and fees quoted by the Bidder shall be firm for a period of twelve (12) months. The bidder shall use the prevailing Rate of Exchange (RoE) based on the South African Reserve Bank at 12:00 on the 12 October 2018, 7 days before closing date) to price imported content offered in this bid.
- 7.7 Rate of Exchange to be used to convert bid price: Rate of exchange to be used in this bid in the conversion of the bid price of the item(s) to South African currency is **US Dollar** as indicated in the table below:-

Rates of exchange	
01/10/2019	

- 7.8 Prices in the pricing schedule of the Contract shall differentiate between foreign and local pricing and shall indicate/substantiate the base rate of exchange (ROE) used to convert the foreign portion to South African currency. Any increase or reduction in the relevant amount as a result of any fluctuation in the rate of exchange or revaluation of currencies shall, irrespective of whether the price is firm or not, be subject to the following conditions:
- 7.9 <u>Fluctuations between contract pricing schedule rates and quotes</u>: Will be fully exposed to ROE adjustments with the ROE determined at the average buy and sell spot rate on quote date based on the South African Reserve Bank rates at 12:00 on the date of the quote.

Currency	Rates of exchange
US Dollar	Average buy and sell spot rate on the quote date

7.10 Fluctuations between quote date and order date: The order amount in South African currency will be placed on the Supplier less, or plus, an amount reflecting any change in the exchange rate exceeding 5% (tolerance rate) compared to the quoted rate, determined at average buy and sell spot rate on quote date based on the South African Reserve Bank rates. In the event where the actual spot rate differs by more than 5% from the quote rate on the date of the order, the supplier my request an updated quote (if more) or the Department my request an updated rate (if less).

- Fluctuations between order date and invoice settlement date: Any further fluctuation in the ROE and the 7.11 cost of taking forward cover, which may occur between the purchaser order and the date of the invoice settlement, shall be absorbed by the Supplier.
- Any request for price changes or rate of exchange variation shall be supported by documentary evidence, 7.12 in the form of proof of the applicable rates on the applicable dates, by providing printouts of the South African Reserve Bank rates
- Applications for price adjustments must be submitted in a formal letter listing the items applicable to the 7.13 adjustment and accompanied by documentary evidence in support of any adjustment claim.

8. **DECLARATION OF INTEREST**

The bidder should submit a duly signed declaration of interest (SBD 4) together with the bid. The declaration of interest is attached as Part 5 - Schedule D.

9. **QUALIFICATIONS OF BIDDERS**

Bidders must submit detailed information including certified copies of certificates together with their bid of their experience in the relevant trade together with present contracts (description of contract, contract period, contact person and telephone numbers). These details should be submitted together with the bid on the form attached as Part 5 - Schedule G.

10. PARTNERSHIPS AND LEGAL ENTITIES

In the case of the bidder being a partnership, close corporation or a company all certificates (CK documents) reflecting the names, identity numbers and address of the partners, members or directors (as the case may be) must be submitted with the bid. These details should be submitted on the form attached as Part 5 – Schedule

CONSORTIUM/JOINT VENTURE 11.

- It is recognized that bidders may wish to form consortia to provide the Services. 11.1
- A bid in response to this invitation to bid by a consortium shall comply with the following requirements:-11.2
 - 11.2.1 It shall be signed so as to be legally binding on all consortium members and must clearly stipulate the terms and conditions;
 - One of the members shall be nominated by the others as authorized to be the lead member and this authorization shall be included in the agreement entered into between the consortium members;
 - The lead member shall be the only authorized party to make legal statements, communicate with the Technical Review Committee and/or the ECDoH and receive instructions for and on behalf of any and all the members of the consortium;
 - A copy of the agreement entered into by the consortium members shall be submitted with the bid. Otherwise, the bid will be disqualified.
 - 11.2.5 Each party to the Consortium must submit a consolidated BBBEE Status Level Verification certificate for every separate bid

12. ORGANISATIONAL PRINCIPLES

The bidder should submit a clear indication of the envisaged authorized organisational principles, procedures and functions for an effective delivery of the required Service at the relevant Institutions with the bid. These details should be submitted on the form attached as Part 5 – Schedule I

13. DETAILS OF THE PROSPECTIVE BIDDERS NEAREST OFFICE TO THE LOCATION OF THE CONTRACT

The bidder should provide full details regarding the bidders nearest office to the Institutions at which the Services are to be provided (see Part 4 of this invitation to bid). These details should be provided on the form attached as Part 5 – Schedule J which completed form, must be submitted together with the bid.

14. FINANCIAL PARTICULARS

Bidder must provide full details regarding its financial particulars and standing, which particulars should be submitted together with the bid on the form attached as <u>Part 5- Schedule K</u>. If no such details are submitted it would be assumed that the bidder is not in good standing with his/her financial institutions and his/her bid may be regarded as non-responsive. Bidders must submit financial statements that are not older than a year to assess financial viability.

15. PREFERENCE POINTS CLAIM FORMS

<u>Part 5 – Schedule L</u> contains the Preference Points Claim Forms in terms of Preferential Procurement Regulations to be completed and signed by the bidder to the extent applicable and returned with this bid.

16. VALIDITY

Bid documentation submitted by the bidder will be valid and open for acceptance for a period of 120 days calendar days from the closing date and time stipulated on the front cover of this invitation to bid.

17. ACCEPTANCE OF BIDS

The ECDoH does not bind itself to accept either the lowest or any other bid and reserves the right to accept the bid which it deems to be in the best interest of the State even if it implies a waiver by the State, the ECDoH, of certain requirements which the ECDoH, considers to be of minor importance and not complied with by the bidder.

18. NO RIGHTS OR CLAIMS

- 18.1 Receipt of the invitation to bid does not confer any right on any party in respect of the Services or in respect of or against the State, the Eastern Cape Provincial Government or the ECDoH. The ECDoH reserves the right, in its sole discretion, to withdraw by notice to bidders any Services or combination of Services from the bid process, to terminate any party's participation in the bid process or to accept or reject any response to this invitation to bid on notice to the bidders without liability to any party. Accordingly, parties have no rights, expressed or implied, with respect to any of the Services as a result of their participation in the bid process.
- 18.2 Neither the State, the ECDoH, nor any of their respective directors, officers, employees, agents, representatives or advisors will assume any obligations for any costs or expenses incurred by any party in or associated with any appraisal and/or investigation relating to this invitation to bid or the subsequent submission of a bid in

DRAFTED BY:	SIGNATIORE	DATE
	Whil would	7 0 /00/
RECOMMENDED BY	A	
REVIEWED BY:		x page
APPROVED BY BSC CHAIRPERSON	du who	a (2/09/10
ADVERT APPROVED BY:	111	12/09/10

response to this invitation to bid in respect of the Services or any other costs, expenses or liabilities of whatsoever nature and incurred by bidders in connection with or arising out of the bid process.

19. NON DISCLOSURE, CONFIDENTIALITY AND SECURITY

- The invitation to bid and its contents are made available on condition that they are used in connection with the bid process set out in the invitation to bid and for no other purpose. All information pertaining to this invitation to bid and its contents shall be regarded as restricted and divulged on a "need to know" bases with the approval of the ECDoH.
- 19.2 In the event that the bidder is appointed pursuant to this invitation to bid such bidder may be subject to security clearance prior to commencement of the Services.

20. ACCURACY OF INFORMATION

- 20.1 The information contained in the invitation to bid has been prepared in good faith. Neither the State, the Eastern Cape Provincial Government, the ECDoH nor any of their respective directors, advisors, officers, employees, agents, representatives make any representation or warranty or give any undertaking express or implied, or accept any responsibility or liability whatsoever, as to the contents, accuracy or completeness of the information contained in the invitation to bid, or any other written or oral information made available in connection with the bid and nothing contained herein is, or shall be relied upon as a promise or representation, whether as to the past or the future.
- 20.2 This invitation to bid may not contain all the information that may be required to evaluate a possible submission of a response to this invitation to bid. The bidder should conduct its own independent analysis of the operations to the extent required to enable it to respond to this bid.

21. COMPETITION

- 21.1 Bidders and their respective officers, employees and agents are prohibited from engaging in any collusive action with respect to the biding process which serves to limit competition amongst bidders.
- 21.2 In general, the attention of bidders is drawn to Section 4(1)(iii) of the Competition Act 1998 (Act No. 89 of 1998) (the Competition Act) that prohibits collusive biding.
- 21.3 If bidders have reason to believe that competition issues may arise from any submission of a response to this bid invitation they may make, they are encouraged to discuss their position with the competition authorities before submitting response.
- 21.4 Any correspondence or process of any kind between bidders and the competition authorities must be documented in the responses to this invitation to bid.

22. RESERVATION OF RIGHTS

- 22.1 Without limitation to any other rights of the ECDoH (whether otherwise reserved in this invitation to bid or under law), the ECDoH expressly reserves the right to:-
 - 22.1.1 Request clarification on any aspect of a response to this invitation to bid received from the bidder, such requests and the responses to be in writing;

- 22.1.1 Amend the biding process, including the timetables, closing date and any other date at its sole discretion;
- 22.1.2 Reject all responses submitted by bidders and to embark on a new bid process.
- 22.1.3 Award the bid to more than one bidder.

23. DECLARATION OF BIDDER'S PAST SUPPLY CHAIN MANAGEMENT PRACTICES

23.1 The bidder must complete the declaration and sign accordingly to submit with the bid. The declaration of bidder's past supply chain management practices is attached as Part 5 – Schedule F

24. EVALUATION CRITERIA

EVALUATION CRITERIA

The 80/20 preference point system as prescribed in the Preferential Procurement Policy Framework Act and its Regulations, shall be used for this contract. Ninety points will be allocated for price, and 10 points for BEE.

23.1 The bid will be evaluated as follows:

- Stage 1: Administrative compliance /pre-qualification
- Stage 2: Compliance to Non-negotiables
- Compliance to specification
- Stage 3: Price and B-BBEE Points

The stages are further detailed below

23.2 EVALUATION CRITERIA

The bid will be evaluated in terms of the 80/20 point system as stipulated in the Revised Preferential Procurement Regulations, 2017. 80 points will be allocated for price and 20 points for attaining the B-BBEE status level of contributor.

$$Ps = 80 \left(1 - \frac{Pt - P\min}{P\min} \right)$$

Where

Ps = points scored for comparative price of bid or offer under consideration.

Pt =Comparative price of bid or offer under consideration.

Pmin = comparative price of lowest acceptable bid or offer.

NB: Bidders are required to, together with their bids submit original and valid B-BBEE status level verification certificates, certified copies or a Sworn Affidavit in the case of EMEs and QSEs in the form prescribed by the DTI to substantiate their B-BBEE rating claims. Obtain the Sworn Affidavit form from www.thedti.gov.za

A bid will not be disqualified from the bidding process if the bidder does not submit a certificate substantiating the B-BBEE status level of contribution or sworn affidavit or is a non-compliant contributor. Such a bidder will score 0 out of maximum of 20 points for B-BBEE.

6	SIGNATUR	DE -			
DRAFTED BY:	TILL		1	DATE	0/.0
RECOMMENDED BY	The first	109		100	1/17
REVIEWED BY:	11111	The	10/3	12/2	717
APPROVED BY BSC CHAIRPERSON	THE STATE OF THE S	wba	*\	12 09	190k
ADVERT APPROVED BY:	1/1	1	2	120	1/4

B-BBEE Status Level of Contributor	Number of points (80/20 system)
1	
	20
2	18
3	14
4	12
5	8
6	6
7	4
8	2
Non-compliant contributor	0

NB: Bidders are required to, together with their bids submit original and valid B-BBEE status level verification certificates or certified copies to substantiate their B-BBEE rating claims.

- A bid will not be disqualified from the bidding process if the bidder does not submit a certificate 24.3 substantiating the B-BBEE status level of contribution or is a non-Compliant contributor. Such a bidder will score 0 out of maximum of 10 points for
- Bidders are required to complete the preference claim form (SBD 6.1), and submit their original and valid B-24.4 BBEE status level verification certificate or a certified copy thereof at the closing date and time of the bid in order to claim the B-BBEE status level points.
- The points scored by a bidder in respect of the level of B-BBEE contribution will be added to the points scored 24.5 for price.
- Only bidders who have completed and signed the declaration part of the preference claim form and who have 24.6 submitted a B-BBEE status level certificate issued by a registered auditor, accounting officer (as contemplated in section 60(4) of the close corporation act, 1984) (act no 69 of 1984) or an accredited verification agency will be considered for preference points.

- The department may, before a bid is adjudicated or at any time, require a bidder to substantiate claims it has 24.7 made with regards to preference.
- The total points scored will be rounded off to the nearest 2 decimals. 24.8
- In the event that two or more bids have scored equal total points, the contract will be awarded to the bidder 24.9 scoring the highest number of preference points for B-BBEE.
- However, when functionality is part of evaluation process and two or more bidders have scored equal points 24.10 including equal preference points for B-BBEE, the contract will be awarded to the bidder scoring the highest functionality.
- Should two or more bids equal in all respects, the award shall be decided by drawing of lots. 24.11
- A contract may, on reasonable and justifiable grounds, be awarded to a bid that did not score the highest number 24.12 of points.

#	Requirements	C	omplied
		Yes	No
В	CSD Registration		140
С	Invitation to Bid (SBD1) completed and signed		
E	Pricing Schedule (SBD 3.1)		
F	Declaration of Interest (SBD 4)		
G	Preferential Points Claim(SBD 6.1)		
Н	Declaration of Past SCM Practices (SBD 8)		
I	Certificate of Independent Bid Determination (SBD9)		
J	Proof of Financial Capacity		
M	JV agreement if applicable		

Stage 1 : Pre-qualification evaluation – Admin Compliance

- The purpose of this pre-qualification evaluation is to determine which bid responses are compliant and non-25.1.1 compliant with the bid conditions issued by the ECDoH as part of the bidding process.
- ECDOH has defined minimum pre-qualification criteria that must be met by the Bidder in order for ECDOH to accept a bid for evaluation. In this regard a pre-evaluation verification will be carried out by ECDOH in order to determine whether a Proposal complies with the provisions of this bid.
- Where the Bidder's bid fails to comply fully with any of the pre-qualification criteria. The following criteria shall apply:
- Reject the Bid in question and not to evaluate it at all;
- give the Bidder an opportunity to submit and/or supplement the information and/or documentation provided by it under its Bid so as to achieve full compliance with the pre-qualification criteria, provided that such information and/or documentation can be provided within a specified period determined by the department, of it being requested by ECDoH and is administrative in nature, as opposed to forming a material part of the Bidder's Bid;

DRAFTED BY:	SIGNATURE	DATE
RECOMMENDED BY	phoop	1/2/09/19
REVIEWED BY:	14.	= 12/9/14
APPROVED BY BSC CHAIRPERSON	Juden	9 12/09/2019
ADVERT APPROVED BY:	The party	12/07/7019

SC

25.2.3 In any event permit the bid to be evaluated, subject to the outstanding information and/or documentation being submitted prior to the award of the Bid.

The following Pre-qualification criteria shall apply:

- 25.2.1 The bid documentation must be completed comprehensively and correctly.
- 25.2.2 Declaration forms (SBD 1, 4, 8, 9, 6.1), etc must be signed.
- 25.2.3 Proof of registration with the Centralized Supplier Database (CSD).
- 25.2.4 Documentary Proof of Financial Resources in the form of Letter of confirmation from the reputable financial institution and / or recent (latest 20 February 2018) audited date stamped financial statements.
- 25.2.5 Radiation Control Board Certificate(current).
- 25.2.6 CE marking
- 25.2.7 ISO 9000 / 13485
- 25.2.8 Accreditation letter from the manufacturer indicating supply, delivery, installation, commissioning and maintenance of equipment offered.

Phase 2: Non -Negotiables

All documents below as requested must be present to prevent exclusion. The exclusion of any of the following documents will nullify the bidder's submission- THESE DOCUMENTS TO BE ATTACHED UNDER THE RELEVANT Part 5 Schedules:

ITEM	REQUEST TENDER TO SUPPLY, DELIVER, COMMISSION OF THE CONTINOUS RENAL REPLACEMENT THERAPY (CRRT) MACHINES AND INTERMITTENT HEMODIALYSIS MACHINE	State Your Offer	Technical Reference/ Index Page Number	Compliance (YES/NO)
SECTION	SPECIFICATION			
1	NON NEGOTIABLE - MEDICAL EQUIPMENT			
1.1	CE number with the directive certificate of approved accreditation body shall be supplied indicating the model specific of equipment offered			
1.2	Device shall be Compliant to IEC 601-1 and IEC 601-2 certification			
1.3	The ISO 9000 or ISO 13485 certificate of			

DRAFTED BY:		DATE	^
RECOMMENDED BY	37	1/0	9/19
REVIEWED BY:	7	12/21	19
APPROVED BY BSC CHAIRPERSON	Jana Jana	12/09	1/2
ADVERT APPROVED BY:	1	12/09	16
U3-19/20-0268-NMA	<i>7</i>	1009	120

	manufacturer shall be attached		
1.4	Radiation control directorate certificate for the model offered to be attached		
1.5	A signed letter from the registered manufacturer (on the Manufacturer letterhead) supporting and underwriting the vendor as the accredited and certificated vendor in South Africa for safe distribution, service and maintenance		
1.6	The Life-expectancy of the equipment offered must be 10 years or better before manufacturer end-of-life. Attach manufacturer letter confirming remaining life-expectancy before end-of life.		
1.7	The technology, including software, of the equipment offered must be recent, meaning must not be due for replacement or upgrade over the 10-years life-expectancy. Attach manufacturer's letter of intent as proof. Upgrade costs during this period shall be carried by the contractor and or		
1.8	manufacturer Minimum of 2-year warranty should be included in the basic price. Attach manufacturer proof		
1.9	in writing. The unit will be supplied with all standard accessories for the unit to be fully functional, which should include the first set (starter pack) of consumables		
1.10	The bidder should highlight other optional accessories that may be needed or additional to the functionality of the unit and this shall not form part of the offer		
.11	The bidder must meet a minimum 90 percent of the specification		

DRAFTED BY:	SIGNATURE	DATE
RECOMMENDED BY	May so	12/83/
REVIEWED BY:	11/12	× prin
APPROVED BY BSC CHAIRPERSON	The second	9/2/09/2
ADVERT APPROVED BY:	100,000	12/09/3

Stage 3: Specification evaluation – See Specifications on Part 4 of this Bid document

Stage 4: Price and Preference Points Evaluation

The bid will be evaluated in terms of the 80/20 point system as stipulated in the Preferential Procurement Regulations, 2017. The 80 points will be allocated for price and 20 points for attaining B-BBEE status level of contributor

- Preference points for this bid shall be awarded for:
 - (a) Price; and
 - (b) B-BBEE Status Level of Contribution.

DRAFTED BY:	SIGNATI	JRE	1	DATE	2
RECOMMENDED BY	MA	en		12	109/19
REVIEWED BY:	111	A		7	ztyle
APPROVED BY BSC CHAIRPERSON	the	1000	119	12/	19/20/9
ADVERT APPROVED BY:	1	100	190	12	109/60

PART 2

Conditions of Contract and Operational Requirements

1. CONTRACT

The contract for the supply of the required Service in terms of this invitation to bid shall come into being on the date of issue of the letter of acceptance of the bidders bid by the Eastern Cape Department of Health (ECDoH) and shall continue in force for a period of 12 months. The bidder is further obliged for the future support while the contract is in force.

2. FEES AND CHARGES

- 2.1 Payment of any consideration in terms of the contract shall not constitute acceptance of any defective or non-conforming Services or otherwise relieve contractor of any of its obligations under the contract.
- 2.2 To the extent that the ECDoH disputes the correctness, nature, extent or calculation of any fees or expenses payable to contractor in terms of the contract, ECDoH shall be entitled to withhold payment of such disputed amounts until such time as such dispute is resolved.

3. GENERAL RESPONSIBILITIES OF THE CONTRACTOR

- 3.1 The ECDoH's operational requirements. The contractor shall, in the provision of the required service, have due regard to the operational requirements of the ECDoH and other parties occupying or operating from the relevant institution, and shall not do, or permit to be done, anything which may negatively impact on such parties' operational requirements.
- 3.2 Problem identification and reporting. The contractor shall be proactive in reporting any matters which it may become aware of which may impact on the business continuity or operations of the ECDoH at the relevant institution, clinic and office. Without detracting from the generality of this statement, contractor shall:-
- 3.3 Other Service Providers The contractor acknowledges that it may be required to provide the Services in conjunction with third party service providers and shall, where requested by the ECDoH, co-operate fully with such persons.
- 3.4 Regulations and statutes The contractor shall, in the provision of the Services observe and comply with all relevant provisions of all applicable legislation and regulations.

3.5 Compliance with procedures.

It is recorded that during the currency of the contract the ECDoH may implement procedures and policies at the relevant Institution. The contractor shall comply fully with any such reasonable procedures and policies, including the permit to work procedures and health and safety procedures.

- 3.6 The contractor shall ensure that it and its personnel shall at all times comply fully with any safety, fire, emergency and security procedures and policies applicable at the relevant Institution.
- 3.7 Should the ECDoH at any time believe that any member of contractor's personnel is failing to comply with any such procedures or policies, the ECDoH shall be entitled to deny such personnel member access to the relevant premises and require contractor to replace such person without delay.

DRAFTED BY:	SIGNATURE /		DATE	, ,
	Nellel.	CAL	n.	199/10
RECOMMENDED BY	4	Cald	(3/	2/
REVIEWED BY:	1/1/10		10/	MA
APPROVED BY BSC CHAIRPERSON	May Ja	DI NO	12/0	9/20/
ADVERT APPROVED BY:	1	page	124,0	9112
U3-19/20-0268-NMA	CASI		1 7/10	100

3.8 Contractor's procedures The contractor shall, upon receipt of written request from the ECDoH or its appointed Technical Support Manager at the relevant Institution

Provide the ECDoH with copies of all contractor's operating procedures and processes relating to the Services;

- 3.9 Provision of Services in clean and tidy manner. The contractor shall ensure that the Services are provided in a clean and tidy manner.
- 3.10 Service reports: The contractor shall, upon written request from the DOH or its appointed. Hospital Manager, provide the DOH with such reports relating to the Service as may be stipulated in the Specifications, or as may be reasonably required be the DOH or its appointed Hospital Manager to determine whether contractor is providing the Services in accordance with the terms and conditions of the contract.

4. HAZARDOUS MATERIALS

The contractor will be held liable for any expenses that may be incurred by the ECDOH as a result of damage to property and injury to personnel as a result of poor quality products.

FIRE RISKS

The contractor shall ensure that its personnel shall, if at any time they believe that any matter constitutes a fire risk, report this immediately to the ECDoH/Institution and take such remedial action as may be necessary.

6. ENERGY MANAGEMENT

The contractor shall comply fully with the energy management strategy implemented at the relevant Institution from time to time and shall provide the Services in an energy efficient manner.

7. OCCUPATIONAL HEALTH AND SAFETY

In this clause the term "Act" shall mean the Occupational Health & Safety Act, No. 85 of 1993, as amended from time to time, (including any act which may take its place should it be repealed during the currency of the agreement between the parties) as read with all regulations and standards promulgated in terms of the former Machinery and Occupational Act, No 6 of 1983, as amended, and all regulations & standards promulgated in terms of the Occupational Health & Safety Act from time to time;

The contractor :-

- acknowledges that he is fully aware of the terms and conditions of the Act;
- acknowledges that he is an employer in its own right with duties and responsibilities as prescribed in the Act;
- agrees to comply with all rules and regulations implemented by or on behalf of the ECDoH at the relevant Institution in covering letter relating to health and safety and will inform the ECDoH immediately should contractor for any reason be unable to comply with the provisions of the Act and such rules and regulations.

8. SERVICE LEVEL AGREEMENT

It is recorded that the ECDoH and the service provider may from time to time agree in writing to additional quality requirements (whether engaged in a service contract or when repair is required out of guarantee without the

DRAFTED BY:	SIGNATURE	· A	DATE	laction
RECOMMENDED BY	1000		14	107/19
REVIEWED BY:	Mille		A 12	MAN
APPROVED BY BSC CHAIRPERSON	W/A	A DO D	10/	09/20
ADVERT APPROVED BY:		A Company	12	09/14

maintenance contract option) and standards relating to the maintenance together with performance measurement provisions, which quality requirements, performance measurement provisions shall be reduced to writing in a service level agreement if required and signed by both parties.

9. PERFORMANCE MEASUREMENT PROVISIONS

9.1 Introduction.

Contractor shall provide the Services during the term of the contract in compliance with the quality and related standards stipulated in the Terms of Reference and the service level agreement (if any) contemplated in clause 11 above.

The provisions of Clause 10 document contains the manner in which contractor's performance will be measured throughout the term of the contract.

- 9.2 Compliance. For purposes of the contract the compliance by contractor with the stipulated responsibilities and service standards will be determined:-
 - with reference to reports provided by contractor;
 - with reference to reports or complaints received from third parties;
 - by means of user satisfaction surveys conducted by ECDoH
 - by means of service reviews, inspections or any audit carried out by or on behalf of the ECDoH.
- 9.3 Records. Contractor shall at all times keep full and accurate records of all Services provided in terms of the contract and shall retain such records for the currency of the contract. Upon termination of the contract such records must be provided to the ECDoH upon request.

9.4 Measurement of performance

- Periodic checks: ECDoH and/or its appointed Technical Support Manager shall carry out periodic checks (the intervals to be determined by ECDoH) the purpose of which shall be to determine whether contractor is providing the Services in accordance with the terms and conditions of the contract if accepted by ECDoH.
- Service complaints: All service complaints, deviations, non-conforming services and suggestions that are reported to contractor by ECDoH, its appointed facilities manager, or any other party shall be given proper and speedy consideration by contractor. The Contractor shall investigate complaints, deviations and non-conforming services in accordance with procedures approved by the ECDoH.
- User satisfaction survey: A user satisfaction survey shall be conducted by ECDoH at such intervals as ECDoH may determine to assess service user satisfaction. The user satisfaction survey shall be conducted in such form and in accordance with such procedures as the parties may agree to in writing from time to time.
- 9.5 Results of checks, audits and surveys ECDoH shall be entitled to utilise the findings of the surveys, checks, audits and reports contemplated above to determine compliance by contractor with the service standards and responsibilities stipulated in the contract. It is recorded that the results of the above checks shall, save to the extent that contractor can prove otherwise be binding on contractor and ECDoH shall be entitled to exercise its remedies stipulated in the contract based on such findings.

DRAFTED BY	SIGNATURE DATE A
DRAFTED BY:	(M) 0 00 18
RECOMMENDED BY	
REVIEWED BY:	The Company of the Co
APPROVED BY BSC CHAIRPERSON	12/19/R
ADVERT APPROVED BY:	12/09/1
U3-19/20-0268-NMA	12/12/20

10. **BREACH AND TERMINATION**

Bidders are referred to Paragraph 23 of General Conditions of Contract (GCC) relating to failure to comply with conditions of this contract.

11. LOSS AND DAMAGE

Contractor hereby indemnifies the State, and will hold the State harmless, against any loss or damages which the State may suffer, or any claims lodged against the State by any third party arising out of or relating to any loss that the State or such third party may suffer as a result of, or arising out of any act or omission of any personnel of contractor or the failure of contractor to provide the Services in accordance with the provisions of the contract.

12. SUB-CONTRACTORS

Contractor may only sub-contract its obligations under the contract with the prior written consent of the ECDoH (or any other authorized authority) and then only to a person and to the extent approved by the ECDoH or such authority and upon such terms and conditions as the ECDoH or such authority require. It is recorded that where such consent is given contractor shall remain liable to ECDoH for the performance of the Services.

PART 3

BID STRATEGY

The department is seeking to engage a suitable supplier in a tender process to SUPPLY, DELIVER, COMMISSION AND MAINTAIN HAEMODIALYSIS MACHINES FOR THE EASTERN CAPE DEPARTMENT OF HEALTH

DRAFTED BY:	SIGNATURE	DATE	1 1
RECOMMENDED BY	Mico	1/2	109/1
REVIEWED BY:	Me a	8 /2	101/10
APPROVED BY BSC CHAIRPERSON	MILLER	12/	09/20/
ADVERT APPROVED BY:		139	

STAGE 3 – SPECIFICATION OF MACHINE 1: CONTINOUS RENAL REPLACEMENT THERAPY MACHINE (CRRT)

3	SUPPLY, DELIVERY, INSTALLATION,& MAINTENANCE COMMISSION, OF CONTINOUS RENAL REPLACEMENT THERAPY MACHINE	State your offer	Technical reference/ index page	Score: 0 or 5	Compliand yes/ no
3.1.2	The unit shall be able to perform				
	the following therapies:				
	 Slow Continuous Ultrafiltration (SCUF) 				
	■ Continuous Veno-Venous				
	Haemofiltration (CVVH)				
	■ Continuous Veno-Venous				1
	Haemodialysis (CVVHD)				
	■ Continuous Veno-Venous				
	Haemodiafiltration				
	(CVVHDF)				
	■ Haemoperfusion				
	■ Plasmapheresis				
3.1.3	The unit shall have a user friendly				
3.1.4	communications interface screen			, i	
3.1.4	All therapy parameters and				7 - 1991
	information shall be displayed on				
3.1.5	the screen.				
3.1.5	All alarm conditions shall be audible				
3.1.6	and visually displayed.				
3.1.0	Remedy or guided remedy for				
	alarm conditions shall be displayed				
3.1.7	on screen.				
3.1.7	Software shall be user friendly and				
	easily negotiated by users. It should				
3.1.8	also be upgradeable The screen shall be splash proof.				
3.1.9	The machine shall be able to				
	retain data for at least 15 minutes in case of a power failure via				
	back-up battery.				
3.1.10	The unit must be able to operate				
	on the local conditions reliable.				
3.1.11	State whether the machine is				
	capable of switching between				
	different modalities of CRRT during treatment without changing the			1	
	disposables. e.g If set-up in				
	CVVHDF it can be stepped				
	down/changed to CVVHD.				
	The unit must incorporate a built-in				
	dose controlled heparin infusion				
	pump capable of continuously				

17	
DRAFTED BY:	SIGNATURE DATE
RECOMMENDED BY	1985/19
REVIEWED BY:	111 Cara 12 12 12 12 12 12 12 12 12 12 12 12 12
APPROVED BY BSC CHAIRPERSON	MARCH 12 18 72
ADVERT APPROVED BY:	10/29/06
MU3-19/20-0268-NMA	12/3/1201

	variable infusion rates, using			
	standard disposable 10,20, 30 ar	nd l		
	50 millilitre syringes with all types	of		
	plungers. If your machine is	, 01		
	capable even for other sizes,			
	please state the sizes.			
0.4.40				
3.1.12	The machine should incorporate	an		
	automated calcium citrate regiona	al		
	anticoagulation system.			
3.1.13				
3.1.14	Weighing System:			
3.1.14	The unit shall be volumetric			
1	controlled and include a weighing system to ensure a volumetric			
	balance loop-back control to the			
1	speed of the ultrafiltration pump.			
3.1.15	The weighing system shall be able			
1	to handle weights of up to at least	^		
	10 kilograms or more.			
3.1.16	The weighing system shall			
	include a single load cell with			
	double channel electronic			
3.1.17	evaluation.			
3.1.17	The accuracy of the weighing system shall be ± 30g (balance)			
	and cyclical test during therapy.			
3.1.18	Alarm protection shall be audible			
	and visual.			
3.1.19	Machine shall automatically go			
	into "bypass" (stop balancing			
1	system) in alarm conditions			
2.4.00	related to the weighing system.			
3.1.20	It shall not be possible to silence			-
	the alarm interval for more than 60 seconds.			
3.1.21				
	Blood Pump:			
3.1.22	The Blood pump shall be a roller			+
	pump (with backup manual			1
	operation) and digitally display flow.			
3.1.23	Blood flow range shall be			
	approximately: 0 – 500 ml/min.			
3.1.24	Arterial Pressure:			
3.1.25	Arterial pressure shall be			
0.1.20	electronically measured by means			
	of a pressure transducer and			
	digitally displayed on screen.			
3.1.26	Measurement range shall be			
	approximately: -400 to ±600			
0.4.0=	mmHg.			
3.1.27	Alarm limits shall be			
	approximately –200 to +100			
3.1.28	mmHg adjustable.			
0.1.20	Acoustic alarm silence shall not be longer than 60 seconds.			
3.1.29				
8890154555-555	Pre-Filter Pressure:			

DRAFTED BY:	SIGNATURE	1	DATE	1.61.5
RECOMMENDED BY	ryu	right 0	12	(0)/(2)
REVIEWED BY:	11/1		17	ang
APPROVED BY BSC CHAIRPERSON	Tury.	Maya	12	09/2019
ADVERT APPROVED BY:		greed	120	09 6

0.4.00	"T				
3.1.30	Machine shall be able to measure			T	
1	pre-filter entry pressure in order to				
1	assist the user to extend the life o	f			
	the filter through timeous warning				
	of build-up in filter.				
3.1.31	The pressure shall be				
	electronically measured by means	;			
	of a pressure transducer and				
	digitally displayed on the screen.				
3.1.32	The measurement range shall be				
	approximately: -400 to ±600			1	
	mmHg.				
3.1.33	Alarm limits must be adjustable 0				
	to ± 400 mmHg.				
3.1.34	Adjustable range for				
	Hemofiltration Therapies				
	approximately: 0 to ±600 mmHg.				
3.1.35	Acoustic alarm silence interval not				
	greater than 60 seconds.				
3.1.36	Venous Pressure Monitor:				
0.4.07					
3.1.37	Must be electronically measured				
	by means of a pressure				
	transducer and digitally displayed				
0.4.00	on the screen.				
3.1.38	Measuring range shall be				
	approximately: -400 to ±600				
	mmHg.				
3.1.39	Acoustic alarm silence interval				
	shall not exceed 60 seconds.				
2.1.40	Safety Air Detector:				
3.1.41	The Safety Air Detector must be				
	an ultrasonic detector.		1		
3.1.42	It must automatically do cyclical				
	checks during therapy.				
3.1.43	It must be able to detect the				
	presence of micro-bubbles as well				
	as micro-foam during therapy, or if				
	the blood level drops below the				
	sensor in the tubing.				
3.1.44	The placement of the Air Detector				
	is such that it will prevent false			1	
	alarms caused by the turbulence				
	in the venous chamber.				
3.1.45	Alarm sensitivity range from 0.2				
	mL to 0.8mL.				
3.1.46	The safety clamp must form part				
	of the unit to close the re-infusion				
	blood line to the patient in case of				
	alarm caused by the Safety Air				
	detector or in all "Blood pump				
	stop" conditions.				
3.1.47	Fluid Circuit (Air Detector):				
3.1.48	The unit shall have an air				
	detection system in the				
	Substitution/Dialysate solution			1	
	flow path in order to warn about				
	Paritin order to waiti about			1	
	"empty bag" conditions.		ı		

DATE 17 /89/10
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
20019
12/09/00/0
1204 6
֡

SC

3.1.49	In alarm conditions the unit must	—				
	go automatically into "Bypass"					
1	mode and Substitution and					
1 50	Ultrafiltration pumps must "Stop"					
3.1.50	Alarms must be both audible and					1
	visual.	1				
2.1.51	Acoustic alarm silence interval					1
	shall not exceed 60 seconds.		(1) (1) (1) (1) (1) (1) (1) (1) (1) (1)			
3.1.52						- 1
	Substitution/Dialysate Pump:					
3.1.53	Shall be a 2 roller (or more)					
	peristaltic pump with manual					
	operation possible and flow rate	1				1
	must be digitally displayed on			1		
	screen.			1	1	1
3.1.54	The pump shall automatically					
100	calibrate in preparation phase.				+	
3.1.55	Flow range:					1
	And the second s			+		
3.1.56	Continuous Therapy:					
	Approximate minimal					
	flow range of 0 to 6000			1		
	ml/hr (CVVH)				1	
	> Approximate minimal				1	1
	flow range of 0 to 40 000	1				1
	flow range of 0 to 12 000	1		1	1	
	ml/hr (CVVHD,	1		1		
3.1.57	CVVHDF)	1		1		
and the second second	Filter Inlet Pressure:			+		
3.1.58	This pressure shall monitor for					
	any obstruction in the dialysate	ĺ		+		
	flow into the filter.	i		1		
3.1.59	Much he also transit it	<u></u>		1		1
. 1.00	Must be electronically measured					
	by means of a pressure					
1.00	transducer and digitally displayed.					1
.1.60	Acoustic alarm silence interval					
	shall not exceed 60 seconds.					
.1.61	Warmer:					
.1.62						
1.02	The unit shall include a dialysate					
,	warming system to prevent					
	hypothermia in patients.				1	1
1.63	Temperature must be adjustable					
1	petween 20°C and 40°C in					
1	Continuous/Intermittent Therapies		/	6		1
	and 20°C and 37°C in Plasma		1	ſ		1
	Therapies.		,	1		1
1.64	Please state the temperature			í		1
	alarm limits and duration of			i —		
- 1	alarm limits and duration of		1	i	1	
	condition required prior to alarm		J	1	1	
	activation.(Example: alarm will		1		1	1
	activate after 10seconds at		1	4		
	41degC or 1 sec at 45deg C)		1	1		1
1.05	Warmer shall automatically					1
1	switch-off in high temperature		1	,		
1 :	alarm conditions, but allow		1	/	1	
1	therapy to continue.		1		1	1
.66	Alarms to be both audible and			1	l .	1
1 2	vieually displayed an the correct					
.67	visually displayed on the screen.			1	l .	
10.000000	Acoustic alarm silence interval shall not exceed 60 seconds.					
1.5	shall not exceed 60 seconds		1	I	i	

DRAFTED BY:	SIGNATURE		1	DATE	
RECOMMENDED BY	refref	cer		12	105/1
REVIEWED BY:	1111			-17	laille
APPROVED BY BSC CHAIRPERSON	Tu C	LA San	29	12/	29 Ro
ADVERT APPROVED BY:	1	7900	رب	134	09/14
U3-19/20-0268-NMA		<u> </u>		129	09/12

3.1.68	Blood Leak Detector:	4-0		
3.1.69	A photometric red sensitive blood leak detector will form part of the filter outlet system of the unit.			
3.1.70	Alarm sensitivity range from 0.35mL/ minute to 0.45mL/minute.			
3.1.71	Unit shall automatically perform zero calibration before every therapy session.			
3.1.72	There after cyclical self-testing during therapy.			
3.1.73	Acoustic alarm silence not longer than 60 seconds.			
3.1.74	Filter Outlet Pressure:			
3.1.75	The unit shall incorporate a detection system in the ultrafiltration circuit in order to prevent obstruction of the ultrafiltration circuit and or full waste bag, thus preventing possible spillage and environment			
3.1.76	Acoustic alarm silence interval			
3.1.77	shall not exceed 60 seconds. Ultrafiltration Pump:			
3.1.78	Must be a two or more roller Peristaltic pump with flow rate digitally displayed on screen.			
3.1.79	Exact pump speed must be regulated: Please state means whereby this is achieved and how verification thereof by alternative means is done. (Example: Volumetric balancing with electronic weighing verification).			
3.1.80	Automatic pump calibration in "Preparation "or priming program.			

PART 4 - SPECIFICATION OF MACHINE 2: INTERMITTENT HEMODIALYSIS MACHINE

3.2	SUPPLY, DELIVERY, COMMISSION OF INTERMITTENT HEMODIALYSIS MACHINE	State your offer	Technical reference/ index page	Score: 0 or 5	Compliance yes / no
3.2.1	The monitor must be at least 15" high- resolution TFT LCD with a touch screen user interface.				
3.2.2	The monitor must be able to rotate 3 axes. At least 45 degrees				
3.2.3	All communication keys must be protected against fluid entry.				
3.2.4	Visual error display must be visible from at least two meters and at a reasonable angle. Remedy must accompany error				

21	A
DRAFTED BY:	SIGNATURE DATE
RECOMMENDED BY	100/19
REVIEWED BY:	W C C C C C C C C C C C C C C C C C C C
APPROVED BY BSC CHAIRPERSON	Mukon 12 00 2
ADVERT APPROVED BY:	12/09/60/9
1U3-19/20-0268-NMA	1 4517 1237 12017

SCN

	display for ease of trouble				
3.2.5	shooting.			1	
3.2.5	The following parameters should				
1	be continuously displayed on		1		
3.2.6	screen:				
0.2.0	Actual venous pressure and alarm limits.				
3.2.7	Actual arterial pressure and				
	alarm limits.				
3.2.8					
	Actual TMP and alarm limits				
3.2.9					
3.2.10	Blood flow rates.				
3.2.10	Tompount				
3.2.11	Temperature of dialysate				
0.2.11	Conductivity				
3.2.12	Conductivity				
	UF rate				
3.2.13	The machine shall automatically				
	perform ultrafiltration				
0011	requirement.				
3.2.14	Time 60				
2.2.15	Time of therapy			1	
2.2.15	Elapsed time				
3.2.16	Liapsed time				
0.2.10	Bicarbonate / acetate dialysis				
3.2.17	The state of acctate dialysis				
	Blood pressure				
3.2.18	The machine shall incorporate				
	operator selectable ultrafiltration		1		
	profiling in the following:-				
	Digressive, progressive and		1		
	linear, as well as sequential ultrafiltration and dialysis				
3.2.19					
1.55	Heparin administration				
3.2.20	OCM (online clearance	_			
	monitoring)				
3.2.21	The equipment must be as				
	adaptable as possible and				
	suitable for use with standard				
	and high-flux disposable capillary dialyzers.				
3.2.22	Machine must be programmed				
	as far as possible to provide the				
	greatest ease and safety in				
	operation.				
3.2.23	The machine must incorporate a				
	quick release universal dialyzer		1		
	holder capable of rotating 180 /		1		
.2.24	360 degrees if possible.			1	
	The machine must incorporate an adjustable infusion pole with				
	multiple drip hooks.				
.2.25	The machine must incorporate				
	an oscillometric automated blood				
	pressure measurement device				
	The state of the s			18	

DRAFTED BY:	SIGNATURE		DATE
RECOMMENDED BY	ful mon		12/09/1
REVIEWED BY:			12-194
APPROVED BY BSC CHAIRPERSON	The last	11/19	12 109 12
ADVERT APPROVED BY:			17/04/1

	and medium, large, extra-large cuff sizes.						
3.2.26	The machine must perform an						
	automatic self-test of all						
220	electronics, valves and						
3.2.27	hydraulics before every dialysis						
0.2.21	The machine must perform a blood side self-test before every						
	therapy to check for defects in						
	disposables						
3.2.28	The machine must perform an						
	auto flush of the dialyzer during						
	priming to ensure maximum de- aeration and removal of ETO /						
	renalin from dialyzer pores.						
3.2.29	A complete electronic history of						
	service, disinfections, alarms						
	and system errors must be kept						
3.2.30	in machine's internal memory. Machine must be able to retain						
0.2.00	patient data for at least twenty						
	minutes during power failure.				1		
3.2.31	State minimum and maximum			_			
	water pressure required to run				1		
3.2.32	the machine. Machine must be specified if run						
0.2.02	on RO water or whether can be						
	used on hard water for short					1	
	periods. This is subjected to RO						
3.2.33	failure etc.						
0.2.00	The machine must come with the incoming water filter that will						
	accommodate the water that is						
0.0.0.1	not purely clean.						
3.2.34	Please include all upgrades						
3.2.35	available for the machine.						
	State upgrade policy for future upgrades.						
3.2.36	The machine must have a						
	continuous online Kt/V clearance						
	monitoring tool which is measured, not calculated.						
3.2.37	The machine must have a						
	patient data card for transfer of						
0.000	data to computer.				1		
3.2.38	The machine must heat dialysate						
9	as required and this must be continuously adjustable with high						
	and low visual and audible						
	alarms. Operator adjustable						
	range required between ±36°C			1			
3.2.39	and ±40°C.						
0.2.39	A cut-out circuit must prevent dialysis at temperatures above						
	40°C.					1	
.2.40	A visual indication must be given			-			
	that the dialysate temperature is						
	in the safe range of 36°C to						
	40°C.						
			10				
	г	2	23		1	/	

DRAFTED BY:	SIGNATUR	E	DA ⁻	TE /
RECOMMENDED BY	a pu	1	17	409/19
REVIEWED BY:	1111			17/9/19
APPROVED BY BSC CHAIRPERSON	May 1	Jax 1	19 12	109/201
ADVERT APPROVED BY:	1	Total	P 13	4109170
MU3-19/20-0268-NMA	H		0	109 12019

dialysate flow at 500ml per minute on standard setting. Adjustable flow range and should include 300ml – 800ml per minute. 3.2.42 The machine must adequately de-aerate dialysate by means of a negative pressure system. Heat based de-aeration is not acceptable. 3.2.43 The dialysate mixing must be checked continuously and automatically in both dialysis motions by a temperature of the dialysis of the conductivity reading is in a pressuring system before being supplied to the dialyser. A visual indication must be given that the conductivity reading is in a presst safe range. Deviation from pre-set values must activate visual and audible alarms. 3.2.44 The conductivity alarms must be activated at ± 0.5mS/cm deviation from pre-set values must activate visual and audible alarms. 3.2.45 A pre-set fail safe back-up conductivity areating must provide at ± 5% variation. 3.2.46 When a conductivity or temperature alarm condition occurs the dialysate supply must at the same time automatically byth press the dialyser. 3.2.47 The machine must have the copability of either being sterilized by chemical means. 3.2.48 Machine to incorporate a dialysate shunt safety interlock by-pass system to prevent accidental dialysis. 3.2.49 The machine must incorporate a dialysate shunt safety interlock by-pass system to prevent accidental dialysis being sterilization. 3.2.50 The machine must retain data on the current treatment in the every control of power failure. 1.2.50 Limited the current reatment in the every control of power failure. 1.50 Limited the current reatment in the every collision of present additional fluid loss requirements dialysis of the machine must retain data on the current treatment in the every collision for the desire and the current reatment in the every collision for the every collision for additional fluid loss requirements dialysis and profiling the course of treatment.	C 0 0 11	T					
minute on standard setting. Adjustable flow range and should include 300ml – 800ml per minute. 3.2.42 The machine must adequately de-serate dialysate by means of a negative pressure system. Heat based de-aerated in snot acceptable. 3.2.43 The dialysate mixing must be checked continuously and automatically in both dialysis modes by a temperature compensated conductivity measuring system before being suppled to the dialysate mixing super the conductivity measuring system before being suppled to the dialysate mixing super personal standard setting and supersonal setting and setting and supersonal setting and super	3.2.41	The machine must control					
Adjustable flow range and should include 300ml = 800ml per minute. 3.2.42 The machine must adequately de-aerate dialysate by means of a negative pressure system. Heat based de-aeration is not acceptable. 3.2.43 The dialysate mixing must be checked continuously and automatically in both dialysis modes by a temperature compensated conductivity measuring system before being supplied to the dialyzer. A visual indication must be given that the conductivity reading is in a present safe range. Deviation from pre-set values must activate visual and audible alams. 3.2.44 The conductivity alams must be activated at ± 0.5 mS/cm deviation from pre-set values. 3.2.45 A pre-set fall safe back-up conductivity alam must operate at ±5% variation. 3.2.46 When a conductivity alam must operate at ±5% variation. 3.2.47 The machine must have the capability of either being stemized by heat or being stemize		dialysate flow at 500ml per					
should include 300ml – 900ml per minute. 3.2.42 The machine must adequately dearered callysate by means of a negative pressure system. Heat based de-serated inlysate by means of a negative pressure system. Heat based de-serated in sort acceptable. 3.2.43 The fidilysate mixing must be checked continuously and automatically in both dialysis modes by a temperature compensated conductivity measuring system before being supplied to the dialyzer. A visual indication must be given that the conductivity patient is supplied to the dialyzer. A visual indication must be given that the conductivity reading is in a preset values must activate visual and audible alarms. 3.2.44 The conductivity alarms must be activated at ± 0.5mS/cm deviation from pre-set values must activate visual and audible alarms. 3.2.45 A pre-set fall safe back-up conductivity alarm must operate at ± 5% variation. 3.2.46 When a conductivity or temperature alarm condition occurs the dialysate supply must at the same time automatically by-pass the dialyzer. 3.2.47 The machine must have the capability of either being sterilized by wheat or being sterilized by chemical means. 3.2.48 Machine to incorporate a dialysis. 3.2.50 The machine must be able to perform high flux dialysis Bidders to state built-in precautions to prevent or additional fluid loss requirements during the current treatment in the event of power failure. 2.2.52 The machine must be teal not the current resement in the event of power failure. 2.2.52 The machine must be relained tata on the current resement in the event of power failure. 2.2.52 The machine must be possible to recalculate or re-adjust for additional fluid loss requirements during the course of treatment.							B
3.2.42 The machine must adequately de-aerate dialysate by means of a negative pressure system. Heat based de-aeration is not acceptable. 3.2.43 The dialysate mixing must be checked continuously and automatically in both dialysis modes by a temperature compensated conductivity measuring system before being supplied to the dialyzer. A visual indication must be given that the conductivity reading is in a preset set sef range. Deviation from pre-set values must activate visual and audible alarms. 3.2.44 The conductivity alarms must be activated at ± 0.5ms/cm deviation from pre-set values. 3.2.45 A pre-set fall safe beck-up conductivity alarm must operate at ± 5% variation. 3.2.46 When a conductivity alarm must operate at ± 5% variation. 3.2.47 The machine must have the capability of either being sterilized by hear or being sterilized by machine must incorporate a dialysate shurt safety interior accidental dialysis. Bridgers to read the prevent accidental dialysis by perform high flux dialysis. Bridgers to read the prevent accidental dialysis by perform high flux dialysis. Bridgers to read the prevent accidental dialysis. Bridgers to read the prevent accidental dialysis. Bridgers to read the prevent of mixture accidental dialysis. Bridgers to read the prevent of mixture accidental classis. The machine must retain data on the event of prover failure. 2.2.52 In the transfirm must be able to perform high flux dialysis. Bridgers to read the prevent of mixture accidental classis to rea							
3.2.42 The machine must adequately dearest elalystes by means of a negative pressure system. Heat based de-aeration is not acceptable. 3.2.43 The dialysate mixing must be checked continuously and automatically in both dialysis modes by a temperature compensated conductivity measuring system before being supplied to the dialyzer. A visual indication must be given that the conductivity reading is in a presst safe range. Deviation from preset values must activate visual and audible alarms. 3.2.44 The conductivity alarms must be activated at ± 0.5mS/cm deviation from pre-set values must activate visual and audible alarms. 3.2.45 A pre-set fall safe back-up conductivity arisem must operate at ± 5% variation. 3.2.46 When a conductivity or temperature alarm condition occurs the dialystes supply must at the same time automatically by-pass the dialyzer. 3.2.47 The machine must have the capability of either being sterilized by heart or being sterilized by heart or being sterilized by heart or being sterilized by chemical means. 3.2.48 Machine to incorporate a dialysis. 3.2.49 Machine to incorporate a dialysis at high safe bicarbonate dialysis. 3.2.50 The machine must incorporate a dialysis sterilization. 3.2.50 The machine must be able to perform high flux dialysis. Bidders to state built-in precautions to prevent or limit back filtration. 3.2.51 The machine must retain data on the current treatment in the event of power failure.		The contract of the contract o					1
de-aerate dialysate by means of a negative pressure system. Heat based de-aeration is not acceptable. 3.2.43 The dialysate mixing must be checked continuously and automatically in both dialysis modes by a temperature compensated conductivity measuring system before that the conductivity reading is in a preset safe range. Deviation from preset values must activate visual and audible alarms. 3.2.44 The conductivity alarms must be activated at ± 0.5mS/cm deviation from preset values must activate visual and audible alarms. 3.2.45 A pre-set fall safe back-up conductivity alarms must be activated at ± 5% variation. 3.2.46 When a conductivity or temperature alarm condition occurs the dialysate supply must at the same time automatically by-pass the dialyzer. 3.2.47 The machine must have the capability of either being sterilized by heart or being sterilized by pheart or being sterilized by heart or being sterilized by chancial means. 3.2.48 Machine to incorporate a dialysis. 3.2.49 The machine must safety interlock by-pass system after bicarbonate dialysis. 3.2.40 The machine must be able to perform high flux dialysis. 3.2.50 The machine must be able to perform high flux dialysis. 3.2.50 The machine must to a perform high flux dialysis. 3.2.51 The machine must rotain data on the current treatment in the event of power failure. 2.2.52 It must be possible to recalculate or re-adjust for a additional fluid loss requirements during the course of treatment.							
a negative pressure system. Heat based de-aeration is not acceptable. 3.2.43 3.2.43 The dialysate mixing must be checked continuously and automatically in both dialysis modes by a temperature compensated conductivity measuring system before being supplied to the dialyzer. A visual indication must be given that the conductivity reading is in a present safe range. Deviation from pre-set values must activate visual and audible alarms. 3.2.44 The conductivity alarms must be adviation from pre-set values. 3.2.45 A pre-set fall safe back-up conductivity alarm must operate at £5% variation. 3.2.46 When a conductivity or temperature alarm condition occurs the dialysate supply must at the same time automatically by-pass the dialyzer. 3.2.47 The machine must have the capability of either being sterilized by heart or heling sterilized by chemical means. 3.2.48 Machine to incorporate decalification mode for cleaning system after bicarbonate dialysis. 3.2.49 The machine must incorporate a dialysate shurth safety interlock by-pass system to prevent accidental dialysis during sterilization. The machine must incorporate a dialysate shurth safety interlock by-pass system to prevent accidental dialysis during sterilization. The machine must beable to perform high flux dialysis. Bidders to state built-in precautions to prevent or limit back filtration. 3.2.50 The machine must retain data on the current treatment in the event of power failure. 2.2.52 It must be possible to recalculate or re-adjust for additional fluid loss requirements during the course of treatment.	3.2.42						
Heat based do-aeration is not acceptable. 3.2.43 The dialysate mixing must be checked continuously and automatically in both dialysis modes by a temperature compensated conductivity measuring system before being supplied to the dialyzer. A visual indication must be given that the conductivity reading is in a present values must activate visual and audible alarms. 3.2.44 The conductivity alarms must be activated at 12 6 ms/cm deviation from pre-set values. 3.2.45 A pre-set fall safe back-up conductivity alarms must be activated at 2 6 ms/cm must operate at 5 % variation. 3.2.46 When a conductivity or temperature alarm condition occurs the dialysate supply must at the same time automatically by-pass the dialyzer. 3.2.47 The machine must have the capability of either being sterilized by heart or being sterilized by heart or being sterilized by chemical means. 3.2.48 Machine to incorporate a dialysis. 3.2.49 The machine must incorporate a dialysis during system after bicarbonate dialysis than the same time automatically by-pass system to prevent accidental dialysis during sterilization. The machine must be able to perform high flux dialysis. 3.2.50 The machine must be able to perform high flux dialysis. Bidders to state built-in precautions to prevent or power failure. 2.2.52 If the machine must retain data on the current treatment in the event of power failure. 2.2.52 If the machine must retain data on the current treatment in the event of power failure.							
acceptable. 3.2.43 The dialysate mixing must be checked continuously and automatically in both dialysis modes by a temperature compensated conductivity measuring system before being supplied to the dialyzer. A visual indication must be given that the conductivity reading is in a present values must activate visual and audible alarms. 3.2.44 The conductivity alarms must be activated visual and audible alarms. 3.2.45 A pre-set fail safe back-up conductivity alarm must operate at ±5% variation. 3.2.46 When a conductivity or temperature alarm condition occurs the dialysate supply must at the same time automatically by-pass the dialyzer. 3.2.47 The machine must have the capability of either being sterilized by heart or being sterilized by chemical means. 3.2.48 Machine to incorporate decalification mode for cleaning system after bicarbonate dialysis. 3.2.49 The machine must incorporate a dialysate shurth safety interiock by-pass system to prevent accidental dialysis during sterilization. 3.2.50 The machine must bable to perform high flux dialysis. Bidders to state built-in precautions to prevent or cleaning sterilization. 3.2.51 The machine must retain data on the current treatment in the event of power failure. 2.2.52 It must be possible to recalculate or re-adjust for additional fluid loss requirements during the course of treatment.		a negative pressure system.					
The dialysate mixing must be checked continuously and automatically in both dialysis modes by a temperature compensated conductivity measuring system before being supplied to the dialyzer. A visual indication must be given that the conductivity reading is in a preset safe range. Deviation from preset values must activate visual and audible alarms. 3.2.44 The conductivity alarms must be activated at ± 0.5mS/cm deviation from preset values. 3.2.45 A pre-set fall safe back-up conductivity alarms must operate at ± 5% variation. 3.2.46 When a conductivity or temperature alarm condition occurs the dialysate supply must at the same time automatically by-pass the dialyzer. 3.2.47 The machine must have the capability of either being sterilized by hear or being sterilized by hear or being sterilized by hear being st							
checked continuously and automatically in both dialysis modes by a temperature compensated conductivity measuring system before being supplied to the dialyzer. A visual indication must be given that the conductivity reading is in a present set safe range. Deviation from pre-set values must activate visual and audible alarms. 3.2.44 The conductivity alarms must be activated at ± 0.5 mS/cm deviation from pre-set values. 3.2.45 A pre-set fall safe back-up conductivity alarm must operate at ± 5% variation. 3.2.46 When a conductivity or temperature alarm condition occurs the dialysate supply must at the same time automatically bypass the dialyzer. 3.2.47 The machine must have the capability of either being sterilized by chemical means. 3.2.48 Machine to incorporate decalification mode for cleaning system after bicarbonate dialysis. 3.2.49 Machine to incorporate a dialysate shunt safety interlock by-pass system to prevent accidental dialysis during sterilization. 3.2.49 The machine must incorporate a dialysate shunt safety interlock by-pass system to prevent accidental dialysis during sterilization. 3.2.50 The machine must be able to perform high flux dialysis. Bidders to state built-in precautions to prevent or limit back filtration. 3.2.51 The machine must retain data on the current treatment in the event of power failure. 2.2.52 It must be possible to recallulate or re-adjust for additional fluid loss requirements during the course of treatment.	0.0.40						
automatically in both dialysis modes by a temperature compensated conductivity measuring system before being supplied to the dialyzer. A visual indication must be given that the conductivity reading is in a preset safe range. Deviation from pre-set values must activate visual and audible alarms. 3.2.44 The conductivity laams must be activated at ± 0.5mS/cm deviation from preset values. 3.2.45 A pre-set fall safe back-up conductivity alarms must perate at ± 5% variation. 3.2.46 When a conductivity or temperature alarm condition occurs the dialysters upon your safe that the capability of either being sterilized by hear or being sterilized by hear or being sterilized by hear or being sterilized by chemical means. 3.2.48 Machine to incorporate dealification mode for cleaning system after bicarbonate dialysis. 3.2.49 The machine must incorporate a dialysate shunt safety interlock by-pass system to prevent accidental dialysis during sterilization. 3.2.50 The machine must be able to perform high flux dialysis. Bidders to state built-in precautions to prevent or limit beach filtration. 3.2.51 The machine must retain data on the current treatment in the event of power failure. 2.2.52 It must be possible to recalculate or re-adjust for additional fluid loss requirements during the course of treatment.	3.2.43	The dialysate mixing must be					
modes by a temperature compensated conductivity measuring system before being supplied to the dialyzer. A visual indication must be given that the conductivity reading is in a present safe range. Deviation from pre-set values must activate at 2.5 c. 5.5 c. 5.5 c. 3.2.44 The conductivity alarms must be activated at 2.0 c. 5.5 c. 6.5 c. 6		checked continuously and					
compensated conductivity measuring system before being supplied to the dialyzer. A visual indication must be given that the conductivity reading is in a pre- set safe range. Deviation from pre-set values must activate visual and audible alarms. 3.2.44 3.2.45 A pre-set fail safe back-up conductivity alarms must be activated at ± 0.5mS/cm deviation from pre-set values. 3.2.46 A pre-set fail safe back-up conductivity alarms must operate at ± 5% variation. 3.2.47 When a conductivity or the dialysate supply must at the same time automatically by-pass the dialyzer. 3.2.47 The machine must have the capability of either being sterilized by chemical means. 3.2.48 Machine to incorporate deciolification mode for cleaning system after bicarbonate dialysis. 3.2.49 The machine must incorporate a dialysis during sterilization. 3.2.50 The machine must be able to perform high flux dialysis. Bidders to state built-in precautions to prevent or limit back filtration. 3.2.51 The machine must retain data on the current treatment in the event of power failure. 1.2.52 Lin must be possible to re calculate or re-adjust for additional fluid loss requirements during the course of treatment. 3.2.53 Software and profiling							
measuring system before being supplied to the dialyzer. A visual indication must be given that the conductivity reading is in a present safe range. Deviation from pre-set values must activate at values must activate at values must activate at values dat 4.0 5mS/cm deviation from pre-set values. 3.2.45 The conductivity alarms must be activated at ±0.5mS/cm deviation from pre-set values. 3.2.46 A pre-set fail safe back-up conductivity alarm must operate at ±5% variation. 3.2.47 The machine must perate at the same time automatically by-pass the dialyzer. 3.2.47 The machine must have the capability of either being sterilized by heart or being sterilized by chemical means. 3.2.48 Machine to incorporate decalcification mode for cleaning system after bicarbonate dialysis. 3.2.49 The machine must incorporate a dialysis during sterilization. 3.2.50 The machine must be able to perform high flux dialysis. Bidders to state built-in precautions to prevent accidental dialysis during sterilization. 3.2.50 The machine must retain data on the current treatment in the event of power failure. 2.2.52 It must be possible to recalculate or re-adjust for additional fluid loss requirements during the course of treatment. 5.54 Software and profiling		componented conductivity					
supplied to the dialyzer. A visual indication must be given that the conductivity reading is in a preset safe range. Deviation from pre-set values must activate visual and audible alarms. 3.2.44 3.2.45 3.2.46 A pre-set fail safe back-up conductivity alarms must be activated at ± 0.5mS/cm deviation from pre-set values. 3.2.46 A pre-set fail safe back-up conductivity alarm must operate at ± 5% variation. When a conductivity or the preparture alarm condition occurs the dialysate supply must at the same time automatically by-pass the dialyzer. 3.2.47 The machine must have the capability of either being sterilized by hear or being sterilized by hear or being sterilized by chemical means. 3.2.48 Machine to incorporate decidification mode for cleaning system after bicarbonate dialysis. 3.2.49 The machine must incorporate a dialysate shunt safety interlock by-pass system to prevent accidental dialysis during sterilization. 3.2.50 The machine must be able to perform high flux dialysis. Bidders to state built-in precautions to prevent or limit back filtration. 3.2.51 The machine must retain data on the current treatment in the event of power failure. It must be possible to recalculate or re-adjust for additional fluid loss requirements during the course of treatment.		measuring eyetom before being	1				
indication must be given that the conductivity reading is in a preset safe range. Deviation from preset values must activate visual and audible alarms. 3.2.44 The conductivity alarms must be activated at ± 0.5mS/cm deviation from pre-set values. 3.2.45 A pre-set fail safe back-up conductivity alarm must operate at ± 5% variation. 3.2.46 When a conductivity or temperature alarm condition occurs the dialysate supply must at the same time automatically by-pass the dialyzer. 3.2.47 The machine must have the capability of either being sterilized by chemical means. 3.2.48 Machine to incorporate decalcification mode for cleaning system after bicarbonate dialysis. 3.2.49 The machine must incorporate a dialysate shunt safety interlock by-pass system to prevent accidental dialysis during sterilization. 3.2.50 The machine must be able to perform high flux dialysis. Bidders to state built-in precautions to prevent in the event of power failure. 2.2.52 It must be possible to recalculate or re-adjust for additional fluid loss requirements during the course of treatment. 3.2.53 Software and profiling		supplied to the dialyzor. A vigual	1				
conductivity reading is in a preset safe range. Deviation from pre-set values must activate visual and audible alarms. 3.2.44 The conductivity alarms must be activated at ± 0.5mS/cm deviation from pre-set values. 3.2.45 A pre-set fall safe back-up conductivity alarm must operate at ± 5% variation. 3.2.46 When a conductivity or temperature alarm condition occurs the dialysate supply must at the same time automatically by-pass the dialyzer. 3.2.47 The machine must have the capability of either being sterilized by heat or being sterilized by heat or being sterilized by chemical means. 3.2.48 Machine to incorporate decaloffication mode for cleaning system after bicarbonate dialysis. 3.2.49 The machine must incorporate a dialysate shunt safety interlock by-pass system to prevent accidental dialysis during sterilization. 3.2.50 The machine must be able to perform high flux dialysis. Bidders to state built-in precautions to prevent or limit back filtration. 3.2.51 The machine must retain data on the current treatment in the event of power failure. 2.2.52 It must be possible to recalculate or re-adjust for additional fluid loss requirements during the course of treatment.		indication must be given that the					
set safe range. Deviation from pre-set values must activate visual and audible alarms. 3.2.44 The conductivity alarms must be activated at ± 0.5mS/cm deviation from pre-set values. 3.2.45 A pre-set fail safe back-up conductivity alarm must operate at ± 5% variation. 3.2.46 When a conductivity or temperature alarm condition occurs the dialysate supply must at the same time automatically by-pass the dialyzer. 3.2.47 The machine must have the capability of either being sterilized by heat or being sterilized by chemical means. 3.2.48 Machine to incorporate decalcification mode for cleaning system after bicarbonate dialysis. 3.2.49 The machine must incorporate a dialysate shunt safety interlock by-pass system to prevent accidental dialysis during sterilization. 3.2.50 The machine must be able to perform high flux dialysis. Bidders to state built-in precautions to prevent or limit back filtration. 3.2.51 The machine must retain data on the current treatment in the event of power failure. 2.2.52 It must be possible to recalculate or re-adjust for additional filtud loss requirements during the course of treatment. 3.2.53 Software and profiling		conductivity reading is in a pre-					
pre-set values must activate visual and audible alarms. 3.2.44 The conductivity alarms must be activated at ± 0.5mS/cm deviation from pre-set values. 3.2.45 A pre-set fail safe back-up conductivity alarm must operate at ± 5% variation. 3.2.46 When a conductivity or temperature alarm condition occurs the dialysate supply must at the same time automatically by-pass the dialyzer. 3.2.47 The machine must have the capability of either being sterilized by heat or being sterilized by heat or being sterilized by chemical means. 3.2.48 Machine to incorporate dealcification mode for cleaning system after bicarbonate dialysis. 3.2.49 Machine must incorporate a dialysate shunt safety interlock by-pass system to prevent accidental dialysis during sterilization. 3.2.50 The machine must be able to perform high flux dialysis. Bidders to state built-in precautions to prevent or limit back filtration. 3.2.51 The machine must retain data on the current treatment in the event of power failure. 2.2.52 It must be possible to recalculate or re-adjust for additional fluid loss requirements during the course of treatment.		set safe range. Deviation from					
Visual and audible alarms. 3.2.44 The conductivity alarms must be activated at ± 0.5mS/cm deviation from pre-set values. 3.2.45 A pre-set fail safe back-up conductivity alarm must operate at ± 5% variation. 3.2.46 When a conductivity or temperature alarm condition occurs the dialysate supply must at the same time automatically by-pass the dialyzer. 3.2.47 The machine must have the capability of either being sterilized by chemical means. 3.2.48 Machine to incorporate decalicification mode for cleaning system after bicarbonate dialysis. 3.2.49 The machine must incorporate a dialysate shunt safety interlock by-pass system to prevent accidental dialysis during sterilization. 3.2.50 The machine must be able to perform high flux dialysis. Bidders to state built-in precautions to prevent or limit back filtration. 3.2.51 The machine must retain data on the current treatment in the event of power failure. 2.2.52 It must be possible to recaldiditional fluid loss requirements during the course of treatment.							
3.2.44 The conductivity alarms must be activated at ± 0.5mS/cm deviation from pre-set values. 3.2.45 A pre-set fail safe back-up conductivity alarm must operate at ± 5% variation. 3.2.46 When a conductivity or temperature alarm condition occurs the dialysate supply must at the same time automatically by-pass the dialyzer. 3.2.47 The machine must have the capability of either being sterilized by heat or being sterilized by chemical means. 3.2.48 Machine to incorporate decalcification mode for cleaning system after bicarbonate dialysis. 3.2.49 The machine must incorporate a dialysate shunt safety interlock by-pass system to prevent accidental dialysis during sterilization. 3.2.50 The machine must be able to perform high flux dialysis. Bidders to state built-in precautions to prevent or limit precautions to prevent or limit precautions to prevent or limit back filtration. 3.2.51 The machine must retain data on the current treatment in the event of power failure. 2.2.52 It must be possible to recalculate or re-adjust for additional fluid loss requirements during the course of treatment.				1			
activated at ± 0.5mS/cm deviation from pre-set values. 3.2.45 A pre-set fail safe back-up conductivity alarm must operate at ± 5% variation. 3.2.46 When a conductivity or temperature alarm condition occurs the dialysate supply must at the same time automatically by-pass the dialyzer. 3.2.47 The machine must have the capability of either being sterilized by heat or being sterilized by heat or being sterilized by chemical means. 3.2.48 Machine to incorporate decalcification mode for cleaning system after bicarbonate dialysis. 3.2.49 The machine must incorporate a dialysate shunt safety interlock by-pass system to prevent accidental dialysis during sterilization. 3.2.50 The machine must be able to perform high flux dialysis. Bidders to state built-in precautions to prevent or limit back filtration. 3.2.51 The machine must teain data on the current treatment in the event of power failure. 2.2.52 It must be possible to recalculate or re-adjust for additional fluid loss requirements during the course of treatment.	3.2.44						
3.2.45 A pre-set fail safe back-up conductivity alarm must operate at ± 5% variation. 3.2.46 When a conductivity or temperature alarm condition occurs the dialysate supply must at the same time automatically by-pass the dialyzer. 3.2.47 The machine must have the capability of either being sterilized by heat or being sterilized by chemical means. 3.2.48 Machine to incorporate decalcification mode for cleaning system after bicarbonate dialysis. 3.2.49 The machine must incorporate a dialysate shunt safety interlock by-pass system to prevent accidental dialysis during sterilization. 3.2.50 The machine must be able to perform high flux dialysis. Bidders to state built-in precautions to prevent or limit back filtration. 3.2.51 The machine must retain data on the current treatment in the event of power failure. 2.2.52 It must be possible to recalculate or re-adjust for additional fluid loss requirements during the course of treatment. 3.2.53 Software and profiling		activated at ± 0.5mS/cm					
conductivity alarm must operate at ± 5% variation. 3.2.46 When a conductivity or temperature alarm condition occurs the dialysate supply must at the same time automatically by-pass the dialyzer. 3.2.47 The machine must have the capability of either being sterilized by heat or being sterilized by chemical means. 3.2.48 Machine to incorporate decalcification mode for cleaning system after bicarbonate dialysis. 3.2.49 The machine must incorporate a dialysate shunt safety interlock by-pass system to prevent accidental dialysis during sterilization. 3.2.50 The machine must be able to perform high flux dialysis. Bidders to state built-in precautions to prevent or limit back filtration. 3.2.51 The machine must retain data on the current treatment in the event of power failure. 2.2.52 It must be possible to re-calculate or re-adjust for additional fluid loss requirements during the course of treatment. 3.2.53 Software and profiling		deviation from pre-set values.					
at ± 5% variation. 3.2.46 When a conductivity or temperature alarm condition occurs the dialysate supply must at the same time automatically by-pass the dialyzer. 3.2.47 The machine must have the capability of either being sterilized by heat or being sterilized by chemical means. 3.2.48 Machine to incorporate decalcification mode for cleaning system after bicarbonate dialysis. 3.2.49 The machine must incorporate a dialysate shunt safety interlock by-pass system to prevent accidental dialysis during sterilization. 3.2.50 The machine must be able to perform high flux dialysis. Bidders to state built-in precautions to prevent or limit back filtration. 3.2.51 The machine must retain data on the current treatment in the event of power failure. 2.2.52 It must be possible to recalculate or re-adjust for additional fluid loss requirements during the course of treatment. 3.2.53 Software and profiling	3.2.45						
3.2.46 When a conductivity or temperature alarm condition occurs the dialysate supply must at the same time automatically by-pass the dialyzer. The machine must have the capability of either being sterilized by hear or being sterilized by chemical means. 3.2.48 Machine to incorporate decalcification mode for cleaning system after bicarbonate dialysis. 3.2.49 The machine must incorporate a dialysate shunt safety interlock by-pass system to prevent accidental dialysis during sterilization. 3.2.50 The machine must be able to perform high flux dialysis. Bidders to state built-in precautions to prevent or limit back filtration. 3.2.51 The machine must retain data on the current treatment in the event of power failure. 2.2.52 It must be possible to recalculate or re-adjust for additional fluid loss requirements during the course of treatment. 3.2.53 Software and profiling		conductivity alarm must operate					
temperature alarm condition occurs the dialysate supply must at the same time automatically by-pass the dialyzer. The machine must have the capability of either being sterilized by heat or being sterilized by heat or being sterilized by chemical means. 3.2.48 Machine to incorporate decalcification mode for cleaning system after bicarbonate dialysis. 3.2.49 The machine must incorporate a dialysis shunt safety interlock by-pass system to prevent accidental dialysis during sterilization. 3.2.50 The machine must be able to perform high flux dialysis. Bidders to state built-in precautions to prevent or limit back filtration. 3.2.51 The machine must retain data on the current treatment in the event of power failure. 2.2.52 It must be possible to re- calculate or re-adjust for additional fluid loss requirements during the course of treatment. 3.2.53 Software and profiling					1		
occurs the dialysate supply must at the same time automatically by-pass the dialyzer. 3.2.47 The machine must have the capability of either being sterilized by heat or being sterilized by heat or being sterilized by chemical means. 3.2.48 Machine to incorporate decalcification mode for cleaning system after bicarbonate dialysis. 3.2.49 The machine must incorporate a dialysate shunt safety interlock by-pass system to prevent accidental dialysis during sterilization. 3.2.50 The machine must be able to perform high flux dialysis. Bidders to state built-in precautions to prevent or limit back filtration. 3.2.51 The machine must retain data on the current treatment in the event of power failure. 2.2.52 It must be possible to recalculate or re-adjust for additional fluid loss requirements during the course of treatment.	3.2.46						
at the same time automatically by-pass the dialyzer. 3.2.47 The machine must have the capability of either being sterilized by heat or being sterilized by chemical means. 3.2.48 Machine to incorporate decalcification mode for cleaning system after bicarbonate dialysis. 3.2.49 The machine must incorporate a dialysate shunt safety interlock by-pass system to prevent accidental dialysis during sterilization. 3.2.50 The machine must be able to perform high flux dialysis. Bidders to state built-in precautions to prevent or limit back filtration. 3.2.51 The machine must retain data on the current treatment in the event of power failure. 2.2.52 It must be possible to recalculate or re-adjust for additional fluid loss requirements during the course of treatment. 3.2.53 Software and profiling					1		
3.2.47 The machine must have the capability of either being sterilized by heat or being sterilized by chemical means. 3.2.48 Machine to incorporate decalcification mode for cleaning system after bicarbonate dialysis. 3.2.49 The machine must incorporate a dialysate shunt safety interlock by-pass system to prevent accidental dialysis during sterilization. 3.2.50 The machine must be able to perform high flux dialysis. Bidders to state built-in precautions to prevent or limit back filtration. 3.2.51 The machine must retain data on the current treatment in the event of power failure. 2.2.52 It must be possible to recalculate or re-adjust for additional fluid loss requirements during the course of treatment. 3.2.53 Software and profiling							
3.2.47 The machine must have the capability of either being sterilized by heat or being sterilized by chemical means. 3.2.48 Machine to incorporate decalcification mode for cleaning system after bicarbonate dialysis. 3.2.49 The machine must incorporate a dialysate shunt safety interlock by-pass system to prevent accidental dialysis during sterilization. 3.2.50 The machine must be able to perform high flux dialysis. Bidders to state built-in precautions to prevent or limit back filtration. 3.2.51 The machine must retain data on the current treatment in the event of power failure. 2.2.52 It must be possible to recalculate or re-adjust for additional fluid loss requirements during the course of treatment. 3.2.53 Software and profiling							
capability of either being sterilized by heat or being sterilized by heat or being sterilized by chemical means. 3.2.48 Machine to incorporate decalcification mode for cleaning system after bicarbonate dialysis. 3.2.49 The machine must incorporate a dialysate shunt safety interlock by-pass system to prevent accidental dialysis during sterilization. 3.2.50 The machine must be able to perform high flux dialysis. Bidders to state built-in precautions to prevent or limit back filtration. 3.2.51 The machine must retain data on the current treatment in the event of power failure. 2.2.52 It must be possible to recalculate or re-adjust for additional fluid loss requirements during the course of treatment. 3.2.53 Software and profiling	3 2 47	The machine must have the					
sterilized by chemical means. 3.2.48 Machine to incorporate decalcification mode for cleaning system after bicarbonate dialysis. 3.2.49 The machine must incorporate a dialysate shunt safety interlock by-pass system to prevent accidental dialysis during sterilization. 3.2.50 The machine must be able to perform high flux dialysis. Bidders to state built-in precautions to prevent or limit back filtration. 3.2.51 The machine must retain data on the current treatment in the event of power failure. 2.2.52 It must be possible to recalculate or re-adjust for additional fluid loss requirements during the course of treatment. 3.2.53 Software and profiling	0.2.47						
sterilized by chemical means. 3.2.48 Machine to incorporate decalcification mode for cleaning system after bicarbonate dialysis. 3.2.49 The machine must incorporate a dialysate shunt safety interlock by-pass system to prevent accidental dialysis during sterilization. 3.2.50 The machine must be able to perform high flux dialysis. Bidders to state built-in precautions to prevent or limit back filtration. 3.2.51 The machine must retain data on the current treatment in the event of power failure. 2.2.52 It must be possible to recalculate or re-adjust for additional fluid loss requirements during the course of treatment. 3.2.53 Software and profiling							
3.2.48 Machine to incorporate decalcification mode for cleaning system after bicarbonate dialysis. 3.2.49 The machine must incorporate a dialysate shunt safety interlock by-pass system to prevent accidental dialysis during sterilization. 3.2.50 The machine must be able to perform high flux dialysis. Bidders to state built-in precautions to prevent or limit back filtration. 3.2.51 The machine must retain data on the current treatment in the event of power failure. 2.2.52 It must be possible to recalculate or re-adjust for additional fluid loss requirements during the course of treatment. 3.2.53 Software and profiling		sterilized by ricat of being	1				
decalcification mode for cleaning system after bicarbonate dialysis. 3.2.49 The machine must incorporate a dialysate shunt safety interlock by-pass system to prevent accidental dialysis during sterilization. 3.2.50 The machine must be able to perform high flux dialysis. Bidders to state built-in precautions to prevent or limit back filtration. 3.2.51 The machine must retain data on the current treatment in the event of power failure. 2.2.52 It must be possible to recalculate or re-adjust for additional fluid loss requirements during the course of treatment. 3.2.53 Software and profiling	3.2.48						
system after bicarbonate dialysis. 3.2.49 The machine must incorporate a dialysate shunt safety interlock by-pass system to prevent accidental dialysis during sterilization. 3.2.50 The machine must be able to perform high flux dialysis. Bidders to state built-in precautions to prevent or limit back filtration. 3.2.51 The machine must retain data on the current treatment in the event of power failure. 2.2.52 It must be possible to recalculate or re-adjust for additional fluid loss requirements during the course of treatment. 3.2.53 Software and profiling							
dialysis. 3.2.49 The machine must incorporate a dialysate shunt safety interlock by-pass system to prevent accidental dialysis during sterilization. 3.2.50 The machine must be able to perform high flux dialysis. Bidders to state built-in precautions to prevent or limit back filtration. 3.2.51 The machine must retain data on the current treatment in the event of power failure. 2.2.52 It must be possible to recalculate or re-adjust for additional fluid loss requirements during the course of treatment. 3.2.53 Software and profiling			1				
dialysate shunt safety interlock by-pass system to prevent accidental dialysis during sterilization. 3.2.50 The machine must be able to perform high flux dialysis. Bidders to state built-in precautions to prevent or limit back filtration. 3.2.51 The machine must retain data on the current treatment in the event of power failure. 2.2.52 It must be possible to re- calculate or re-adjust for additional fluid loss requirements during the course of treatment. 3.2.53 Software and profiling							
dialysate shunt safety interlock by-pass system to prevent accidental dialysis during sterilization. 3.2.50 The machine must be able to perform high flux dialysis. Bidders to state built-in precautions to prevent or limit back filtration. 3.2.51 The machine must retain data on the current treatment in the event of power failure. 2.2.52 It must be possible to re- calculate or re-adjust for additional fluid loss requirements during the course of treatment. 3.2.53 Software and profiling	3.2.49	The machine must incorporate a					
accidental dialysis during sterilization. 3.2.50 The machine must be able to perform high flux dialysis. Bidders to state built-in precautions to prevent or limit back filtration. 3.2.51 The machine must retain data on the current treatment in the event of power failure. 2.2.52 It must be possible to recalculate or re-adjust for additional fluid loss requirements during the course of treatment. 3.2.53 Software and profiling		dialysate shunt safety interlock					
sterilization. 3.2.50 The machine must be able to perform high flux dialysis. Bidders to state built-in precautions to prevent or limit back filtration. 3.2.51 The machine must retain data on the current treatment in the event of power failure. 2.2.52 It must be possible to recalculate or re-adjust for additional fluid loss requirements during the course of treatment. 3.2.53 Software and profiling		by-pass system to prevent					
3.2.50 The machine must be able to perform high flux dialysis. Bidders to state built-in precautions to prevent or limit back filtration. 3.2.51 The machine must retain data on the current treatment in the event of power failure. 2.2.52 It must be possible to recalculate or re-adjust for additional fluid loss requirements during the course of treatment. 3.2.53 Software and profiling		accidental dialysis during					
perform high flux dialysis. Bidders to state built-in precautions to prevent or limit back filtration. 3.2.51 The machine must retain data on the current treatment in the event of power failure. 2.2.52 It must be possible to re- calculate or re-adjust for additional fluid loss requirements during the course of treatment. 3.2.53 Software and profiling							
Bidders to state built-in precautions to prevent or limit back filtration. 3.2.51 The machine must retain data on the current treatment in the event of power failure. 2.2.52 It must be possible to recalculate or re-adjust for additional fluid loss requirements during the course of treatment. 3.2.53 Software and profiling	3.2.50						
precautions to prevent or limit back filtration. 3.2.51 The machine must retain data on the current treatment in the event of power failure. 2.2.52 It must be possible to recalculate or re-adjust for additional fluid loss requirements during the course of treatment. 3.2.53 Software and profiling				1			
back filtration. 3.2.51 The machine must retain data on the current treatment in the event of power failure. 2.2.52 It must be possible to recalculate or re-adjust for additional fluid loss requirements during the course of treatment. 3.2.53 Software and profiling				1			
3.2.51 The machine must retain data on the current treatment in the event of power failure. 2.2.52 It must be possible to recalculate or re-adjust for additional fluid loss requirements during the course of treatment. 3.2.53 Software and profiling				1			
the current treatment in the event of power failure. 2.2.52 It must be possible to re- calculate or re-adjust for additional fluid loss requirements during the course of treatment. 3.2.53 Software and profiling	3 2 51			1			
event of power failure. 2.2.52 It must be possible to recalculate or re-adjust for additional fluid loss requirements during the course of treatment. 3.2.53 Software and profiling	0.2.01			1			
2.2.52 It must be possible to recalculate or re-adjust for additional fluid loss requirements during the course of treatment. 3.2.53 Software and profiling							
calculate or re-adjust for additional fluid loss requirements during the course of treatment. 3.2.53 Software and profiling	2.2.52						
additional fluid loss requirements during the course of treatment. 3.2.53 Software and profiling	02						
during the course of treatment. 3.2.53 Software and profiling				1			
3.2.53 Software and profiling							
24	3.2.53						
			24	<u>_</u>	7		
I DICHATUKO / I DIATE		I	24	SIGNATURE	1	DATE .	

DRAFTED BY: RECOMMENDED BY REVIEWED BY: APPROVED BY BSC CHAIRPERSON ADVERT APPROVED BY:

SCMU3-19/20-0268-NMA

3.2.54	It would be professed that the					
3.2.54	It would be preferred that the machine has an integrated					
	'STANDBY' mode to prevent					
	waste of water, concentrate and					
	electricity at the end of priming					
	and prior to patient connection.					
	Deactivation of standby must be user selectable					
3.2.55	The following software function					
	must be available on the					
	machine:					
3.2.56	Data management system –					
3.2.57	patient disk. Kt/V calculation					
3.2.58						4440 TO TO TO TO THE REAL PROPERTY OF THE PARTY OF THE PA
3.2.59	UF profiling.					
3.2.60	Sodium profiling.					
50.0000000	Dialysate flow settings.					
3.2.61	Heparin bolus and Saline bolus volume monitoring					
3.2.62	Blood pump					
3.2.63	Blood flow rate must be					
3.2.64	adjustable: 0-500ml/min					
3.2.04	The blood pump head must be automatically tested during					
	priming for changes in pump					
	head's roller tension.					
3.2.65	The pump must be sturdy and					
	the bloodline guiding tracks must not be easily bent.					
3.2.66	The machine must provide an					
	audio and visual alarm should					
	the blood pump cover be opened					
	and the blood must cease to					
	operate, manual operation of the blood pump must form part of					
	the unit.					
3.2.67	The machine must incorporate					
	roller pump heads with				j.	
	removable heads to facilitate cleaning.					
3.2.68	Safety air detector.					
3.2.69	The machine must incorporate					
0.2.00	an ultrasonic air-foam detector					
	with automatic venous bloodline					
	clamp and blood pump stop with					
3.2.70	audible and visual alarms.					
3.2.70	State sensitivity of air detector for flow rates:					
	0-250ml/min					
	250-300ml/min					
2 2 74	At >300ml/min					
3.2.71	SAD/air detector should incorporate a red sensor able to					
	distinguish blood and saline.					
3.2.72	Blood leak detector.					
3.2.73	A red sensitive blood leak					
	detector with audible and visual					
	Г	25	SIGNATURE	7	DATE	

A	
SIGNATURE DATE	1,19
901	17
Will Charles and a constant	119
10 Les 2 12 00	10/0
12/04/	OF
	SIGNATURE DATE TO 9 TO

	plarm must be in a must be			
	alarm must be incorporated in the system.			
3.2.74	Sensitivity of blood leak detector			
	of blood / litre of dialysate range from 0.35mL/ minute to			
	0.45mL/minute.			
3.2.75	A blood leak alarm condition		 	
	must switch off the blood pump and bypass dialysate flow from			
	the dialyser. It must be possible			
	to deactivate the acoustic alarm			
	(for a blood leak) for no longer			
	than 30sec., alarm itself may not be bridgeable.			
3.2.76	Pressure measurement.			
3.2.77	The following pressure must be			
	automatically tested prior to the			
	start of each therapy: • Venous Pressure			
	Sensor			
	 Arterial Pressure 			
	Sensor			
3.2.78	Arterial Pressures range from -			
	400 to 400 mmHg:			
3.2.79	Venous Pressures range from 0			
0.2.70	to 390mmHg:			
0.0.00				
3.2.80	Transmembrane Pressure range from 100 to 700mmHg:			
3.2.81	State if machine continuously			
	monitors and gives early warning			
	in case of clotting and how it monitors this			
	monitors tris			
3.2.82	Pressure limit window should be			
	automatically adjusted by machine in relationship with			
	patient's individual pressure			
3.2.83	Heparin			
3.2.84	The machine should incorporate			
	a syringe driver, or similar, for			
3.2.85	Heparin administration Heparin syringe driver must be			
	dose controlled and/or			
3.2.86	volumetric controlled			
J.Z.00	Heparin administration should be able to administrate Heparin			
	Bolus.		1	
3.2.87	The machine must have the			
	option for dialysis without heparin administration			
3.2.88	Concentrate			
3.2.89	The machines must be able to			
	mix acetate concentrate at a			
	ratio of 1:34			
		•		

26	SIGNATURE	A DATE
DRAFTED BY:	1/4/	DATE
RECOMMENDED BY	1911	707V17
REVIEWED BY:	MI Cha To	2 /2/19
APPROVED BY BSC CHAIRPERSON	The Total	2 19 08 2
ADVERT APPROVED BY:		170916
U3-19/20-0268-NMA		10 3 201

3.2.90	The weekings of the training				
3.2.90	The machines must be able to mix acid and Bicarbonate				
	concentrate at set ratios of 1:32,				
	77:1,22 as well as variable ratios				
3.2.91	The machine must be able to				
0.2.01	perform bicarbonate and				
	acetate haemodialysis with all				
	MCC registered concentrates				
	available in South Africa.				
3.2.92	The initial calibration and two				
	subsequent calibrations of the				
	machine for a particular				
	concentrate must be included in				
	the purchase price of the				
	machine. This must include				
	acetate and bicarbonate				
	calibration				
3.2.93	The proportioning system must				
	have the option of selecting			=	
	concentrate from more than 10				
	different MCC registered				
3.2.94	concentrates in South Africa				
5.2.34	The machine must be capable of utilizing both liquid and powder				
	bicarbonate				
3.2.95	De-aeration of dialysate should				
	be by means of controlled				
	negative pressure				
3.2.96	Conductivity				
3.2.97	The conductivity alarm must				
0.2.07	activate if "out of specification"				·
	and / or contaminated				
	concentrate is used.				
3.2.98	Activation of the conductivity				
	alarm must result in an audio				
	and visual signal and the blood				
	pump must continue to be				
	operational. The machine must				
	now be in a state of bypass and				
	there must be no dialysate				
2.2.00	delivery into the dialyser.				
3.2.99	The dialysate mixing must be				
	checked continuously and automatically by a temperature				
	compensated conductivity		1	1	
	measuring systems before				
	supply to dialyser	8	1		
3.2.100	Dialysate Flow				
3.2.101	The machine must have an				
J.E. 101	easily variable				
	dialysate flow of 300 (or less) to		- 1		
	800ml/min				
3.2.102	Dialysate flow should be				
	adjustable according to patient				
	specific needs				
3.2.103	The dialysate flow should be				
	constant during dialysis, without				
	fluctuations in the flow, to	1 1			

27	<u>a</u>	1			
DRAFTED BY:	SIGNATURE		DATE	000/	100
RECOMMENDED BY	To the second		16		1
REVIEWED BY:	Marian	avice	,2	09	100
APPROVED BY BSC CHAIRPERSON	hilly	220	2	09/	1
ADVERT APPROVED BY:	T EX		12	09	12019
MU3-19/20-0268-NMA	1 /		10		

SCM

	prevent back filtration and/or			****	
1	therapy interruptions				
3.2.104	Temperature				
3.2.105	Andrews - Control of the Control of				
	The dialysate temperature must be adjustable				
3.2.106	Dialysate temperature should be adjustable for the duration of the therapy				
3.2.107	Temperature must be adjustable between 35°C and 40°C				
2.2.108	A cut-out circuit must prevent Dialysate temperatures above 40°C				
3.2.109	Ultrafiltration Control				
3.2.110	The machine must be volumetric controlled with profile volume removal				
3.2.111	The monitor must display the volume of fluid Already removed.				
3.2.112	UF volume must be adjustable during therapy		-		
3.2.113	The monitor must display the time elapsed since the commencement of dialysis				
3.2.114	The monitor must display the volume of fluid remaining until the end of dialysis				
3.2.115	The machine must be able to perform and profile Sequential ultrafiltration (SUF) or isolated ultra filtration (IUF)				
3.2.116	Sodium Profiling				
3.2.117	The machine must be able to profile sodium				
3.2.118	The machine must be able to display sodium, bicarbonate and final conductivity				
3.2.119	Alarms				
3.2.120	Alarms must be both visual and audible with the audible (being adjustable in terms of volume)				
3.2.121	The alarm must be integrated with the functioning of the dialysis machine and must ensure that the machine goes into bypass or ensure that the blood pump stops, where applicable, during alarm condition				
3.2.122	The machine must be able to retain an alarm				
		28			

28	2 1			
DRAFTED BY:	SIGNATURE	DATE	100	110
RECOMMENDED BY	Charles Control	- /-	- W	121
REVIEWED BY:	My as assa	12	09/	2010
APPROVED BY BSC CHAIRPERSON	M Mode	12	100	120
ADVERT APPROVED BY:		12	09/	1501
U3-19/20-0268-NMA	1, 1	+	0-1	120

SCM

	History					1	_
3.2.123			(1)				
0.2.120	The following should be covered by visual and audible alarms:						
	by vioual and addible alainis.						
	 Failure of mains and 			1	E.		
	battery operation						
	Water Pressure	1					
	Dialysate Pressure					1	
	Venous pressure						
	 Arterial pressure 						
	Air Detector						
	 Dialysate temperature 						
	 Transmembrane 						1
	pressure						
	Blood leak detector						
	 Degassing pressure 						
	Ultrafiltration pump						
	Dialysate flow						
	Sodium conductivity				4		
	Bicarbonate						
	conductivity • Final mixing ratio and/or			1			
	deviation of dialysate			1			
	pH - "Out of Specification"						
	and /or	1					
	contaminated concentrate						
	q Heparin pump				1		
3.2.124	The machine must give a						
	warning when and if conditions						
3.2.125	for back filtration are possible The cause of an alarm condition						
0121120	must be						
	displayed on screen, e.g.			1			
	Heparin pump			1			
	not on, time has elapsed etc.						
3.2.126	Trouble shooting messages with						
	respect to						
	alarm conditions must be						
	displayed						
	e.g. Press heparin on, press start						
3.2.127	Disinfection and					100	
	Decalcification			1			
3.2.128	The machine must be able to be						
	sterilized by						
	chemical means as well as by						
	heat (display last disinfection						
3.2.129	date)						
5.2.129	The machine must have the option of a rinse cycle						
3.2.130	The machine must have the						
.2	option of a long rinse cycle						
3.2.131	The machine must have the						
	option of a						
	hot chemical rinse cycle. State				1		
	chemical agent, temperature.						
	microbial coverage, dwell and						
	rinse time	+5			5		
	r	29		1	1		

3.2.132	The machine must have the	
	option of a	
	cold chemical rinse cycle. State	
	chemical	
	agent, temperature, microbial	
	coverage,	1
	dwell and rinse time	
3.2.131	Sterilant ports and connectors	
	must be corrosion proof	
3.2.132	The machine must incorporate a	
	dialysate	
	shunt safety interlock – bypass	
	system to prevent accidental	
	dialysis during sterilization	
3.2.133	The inclusion of Safety Data	
	Sheets for	
	chemical disinfection /	
	sterilization	
	must be included	

EQUIPMENT GUARANTEES AND SERVICE	COMMENTS	
SPECIFICATIONS FOR BOTH MACHINES	COMMENTS	COMPLY
		<u>Y / N</u>
Equipment must be able to accommodate the		
power supply problems in Mthatha		
No part shall be second hand or refurbished.		
Tender price to include delivery, installation,		
commissioning, two -year warranty and		
training. Acceptance of the equipment will only		
take place after commissioning of the		
equipment.		
The after sales and repairs must carry a twelve		
months guarantee against poor workmanship		
and latent defects and parts. A fully		
comprehensive preventative maintenance,		
service and repair plan including all costs must		
be included in the warranty. Software updates		
and upgrades to be included. This warranty		
will commence after formal acceptance and		
handover of the equipment and successful		
testing and acceptance by the Health		
Technology Services – Clinical Engineering. The successful bidder must arrange with the		
Health Technology Services – Clinical		
Engineering, the notice must be two weeks		
before commissioning the equipment at the		
respective hospital / institution.		
The successful bidder must arrange for an		
acceptance test of the equipment. A		
completed certified copy of this specification		
must be submitted with the equipment when		
the acceptance test(s) is to be undertaken. A		
copy of the acceptance test must be forwarded		
to the Health technology unit of the particular		
institution.		
The recommended number of services per		
annum must be included during and up until		
the end of the guarantee period and all costs		
	30	

30	1	
DRAFTED BY:	SIGNATURE/	DATE 12/08/10
RECOMMENDED BY	The state of the s	> NO VIEW
REVIEWED BY:	M. assena	12/09/201
APPROVED BY BSC CHAIRPERSON	Ju the less	12/09/7019
ADVERT APPROVED BY:		12/09/120/
ALI2-10/20-0260 NIMA		1120

SCMU3-19/20-0268-NMA

roloted to the annulation of the state of		
related to the provisions of such service/s will		
be for the bidder's account. The bidder must		
state the number of services that will be		
provided during and up to the end of the		
guarantee period.		
Software changes to the equipment which are		
corrective in nature and initiated due to		
software errors, regulatory requirements or		
safety reasons, shall be delivered and installed		
at no charge for the life of the equipment.		
Response time for service / repair must be		
within 24 hours.		
Supply the name, address, and telephone		
number/s of the service department.		
Toohnicion(a) must be surelified and for		
Technician(s) must be qualified and factory		
equivalent trained to deal with the service,		
repair and calibration of the equipment quoted		
on. NB proof of factory (or equivalent) training		
must be submitted with this bid/quotation offer.		
The bidder must state how many technicians		
they have permanently employed and their		
names and contact numbers must be supplied.		
State if the technicians are in the direct employ		
of the bidder.		
If the equipment is taken away for repairs during		
the guarantee period, a loan set must be		
supplied for use by the institution for the		
duration of the repairs.		
The up-time of the unit must be better than		
98%, excluding scheduled preventative		
maintenance and software upgrades,		
measured on a quarterly basis. The percentage		
lower than 98% will be added to the warrantee		
period. A sliding scale penalty clause will form		
part of the service contract. This will result in the		
maintenance payment being reduced by a pro		
rata amount that the up-time is less than 98%.		
Up-time is defined as follows:		
24/7: i.e. 365days times 24 hours = 8760 hours.		
A down time of 2% relates to 175 hours per		
annum.		
USER AND TECHNICAL TRAINING		
The successful bidder must provide user		
training in the operation of the unit at no extra		
cost to the final bid price to this department.		
Bidders must detail the training that would be	1	
offered and indicate who would offer the		3 (
training.		
The successful bidder must provide local		
training for Eastern Cape Department of		
Health technicians at the locality of purchase,		1
on the:		1
No. of the Control of		
ound alon,		
maintenance,		
service and		
 Repair of the quoted product. The 		1
quality and level of the training must		
be equivalent to the manufacturer's		
	Λ	
	31	
	SIGNATURE	DATE

31				
DRAFTED BY:	SIGNATURE/	DATE	100	10
RECOMMENDED BY		17	100	XIZ
REVIEWED BY:	VIII a Dana	12	00	120
APPROVED BY BSC CHAIRPERSON	him when -	12	1	tale
ADVERT APPROVED BY:		12/	79	120/6
U3-19/20-0268-NMA		1-1	9	

SC

		A STATE OF THE STA
original factory training and any	The second of th	
costs incurred to provide this training		
will be for the bidder's account. A		
certificate of competency must be		
issued on the successful completion		
of the training. The training must be		
provided by the successful bidder		
within three (3) months from date of		
initial supply and delivery of the		
quoted equipment to the department. Bidders must note that dedicated test		
equipment, spare parts and any special tooling required for the upkeep and maintenance of		
the equipment quoted on must be available to		
the Health Technology Services		
The successful bidder must bring its own tools		
during schedule service or any maintenance		
that needs to be performed in the institution.		
Complete original service / repair manual book		
or CD copies in English must be supplied. The		
manual should include the following		
information:		
Fault finding guide.		
Circuit diagrams / schematics.		
Circuit descriptions and PCB layouts.		
Calibration guide.		
Part numbers.		
Exploded diagram of mechanical		
parts / panels.		
γαιτο / γαιτοίο.		

32	A
DRAFTED BY:	SIGNATURE/ DATE
RECOMMENDED BY	The state of the s
REVIEWED BY:	11/1/2 12/19/2019
APPROVED BY BSC CHAIRPERSON	W. Weda 209 7019
ADVERT APPROVED BY:	1209/201
SCMU3-19/20-0268-NMA	

Phase 3: Note:

Description % of available points Specification compliance (most complete and compliant = 90%)
BBBEE Compliance 1 80% 2 20% Total Total for phase 3

100%

33	Ω /
DRAFTED BY:	SIGNATURE DATE
RECOMMENDED BY	17/19/19
REVIEWED BY:	1979
APPROVED BY BSC CHAIRPERSON	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
ADVERT APPROVED BY:	12/00/00
IU3-19/20-0268-NMA	109/20



Schedule A Government Procurement General Conditions of Contract

Annexure A

NOTES

The purpose of this document is to:

- (i) Draw special attention to certain general conditions applicable to government bids, contracts and orders; and
- (ii) To ensure that clients be familiar with regard to the rights and obligations of all parties involved in doing business with government.

In this document words in the singular also mean in the plural and vice versa and words in the masculine also mean in the feminine and neuter.

- The General Conditions of Contract (GCC) will form part of all bid documents and may not be amended.
- Special Conditions of Contract (SCC) relevant to a specific bid, should be compiled separately for every bid (if applicable) and will supplement the General Conditions of Contract. Whenever there is a conflict, the provisions in the SCC shall prevail.

SIGNATURE/ DATE
Mr (es a vi Deglo) 10
14. W202 12/10/17 701
1000

SCMU3-19/20-0268-NMA

TABLE OF CLAUSES

- 1. Definitions
- 2. Application
- 3. General
- 4. Standards
- 5. Use of contract documents and information; inspection
- 6. Patent rights
- 7. Performance security
- 8. Inspections, tests and analysis
- 9. Packing
- 10. Delivery and documents
 11. Insurance
- 12. Transportation
- 13. Incidental services
- 14. Spare parts
- 15. Warranty 16. Payment 17. Prices

- 18. Contract amendments
- 19. Assignment
- 20. Subcontracts
- 21. Delays in the supplier's performance
- 22. Penalties
- 23. Termination for default24. Dumping and countervailing duties
- 25. Force Majeure
- 26. Termination for insolvency
- 27. Settlement of disputes
- 28. Limitation of liability
- 29. Governing language 30. Applicable law
- 31. Notices
- 32. Taxes and duties

35	A
DRAFTED BY:	SIGNATURE DATE
RECOMMENDED BY	1000
REVIEWED BY:	11 01 01001 1001
APPROVED BY BSC CHAIRPERSON	W who : 12 6 7
ADVERT APPROVED BY:	1009/20
U3-19/20-0268-NMA	100 100

General Conditions of Contract

- 1. Definitions 1. The following terms shall be interpreted as indicated:
 - 1.1 "Closing time" means the date and hour specified in the bidding documents for the receipt of bids.
 - 1.2 "Contract" means the written agreement entered into between the purchaser and the supplier, as recorded in the contract form signed by the parties, including all attachments and appendices thereto and all documents incorporated by reference therein.
 - 1.3 "Contract price" means the price payable to the supplier under the contract for the full and proper performance of his contractual obligations.
 - 1.4 "Corrupt practice" means the offering, giving, receiving, or soliciting of anything of value to influence the action of a public official in the procurement process or in contract execution.
 - "Countervailing duties" are imposed in cases where an enterprise abroad is subsidized by its government and encouraged to market its products internationally.
 - "Country of origin" means the place where the goods were mined, grown or produced or from which the services are supplied. Goods are produced when, through manufacturing, processing or substantial and major assembly of components, a commercially recognized new product results that is substantially different in basic characteristics or in purpose or utility from its components.
 - 1.7 "Day" means calendar day.
 - 1.8 "Delivery" means delivery in compliance of the conditions of the contract or order.
 - 1.9 "Delivery ex stock" means immediate delivery directly from stock actually on hand.
 - 1.10 "Delivery into consignees store or to his site" means delivered and unloaded in the specified store or depot or on the specified site in compliance with the conditions of the contract or order, the supplier bearing all risks and charges involved until the supplies are so delivered and a valid receipt is obtained.
 - 1.11 "Dumping" occurs when a private enterprise abroad market its goods on own initiative in the RSA at lower prices than that of the country of origin and which have the potential to harm the local industries in the RSA.
 - 1.12 "Force majeure" means an event beyond the control of the supplier and not involving the supplier's fault or negligence and not foreseeable.
 - Such events may include, but is not restricted to, acts of the purchaser in its sovereign capacity, wars or revolutions, fires, floods, epidemics, quarantine restrictions and freight embargoes.
 - 1.13 "Fraudulent practice" means a misrepresentation of facts in order to influence a procurement process or the execution of a contract to the detriment of any bidder, and includes collusive practice among bidders (prior to or after bid submission) designed to establish bid prices at artificial non-competitive levels and to deprive the bidder of the benefits of free and open competition.
 - 1.14 "GCC" means the General Conditions of Contract.

36	SIGNATURE /	I DATE
DRAFTED BY:	1 Aul Control	DATE
RECOMMENDED BY	The state of the s	- 7 SX X
REVIEWED BY:	MIN DESTRUCTION	THE STATE OF THE S
APPROVED BY BSC CHAIRPERSON	The state of the	12 68 12
ADVERT APPROVED BY:		12/09/6
U3-19/20-0268-NMA	4	12109/120

- 1.15 "Goods" means all of the equipment, machinery, and/or other materials that the supplier is required to supply to the purchaser under the contract.
- "Imported content" means that portion of the bidding price represented by the cost of components, parts or materials which have been or are still to be imported (whether by the supplier or his subcontractors) and which costs are inclusive of the costs abroad, plus freight and other direct importation costs such as landing costs, dock dues, import duty, sales duty or other similar tax or duty at the South African place of entry as well as transportation and handling charges to the factory in the Republic where the supplies covered by the bid will be manufactured.
- 1.17 "Local content" means that portion of the bidding price which is not included in the imported content provided that local manufacture does take place.
- 1.18 "Manufacture" means the production of products in a factory using labour, materials, components and machinery and includes other related value-adding activities.
- 1.19 "Order" means an official written order issued for the supply of goods or works or the rendering of a service.
- 1.20 "Project site," where applicable, means the place indicated in bidding documents.
- 1.21 "Purchaser" means the organization purchasing the goods.
- 1.22 "Republic" means the Republic of South Africa.
- 1.23 "SCC" means the Special Conditions of Contract.
- 1.24 "Services" means those functional services ancillary to the supply of the goods, such as transportation and any other incidental services, such as installation, commissioning, provision of technical assistance, training, catering, gardening, security, maintenance and other such obligations of the supplier covered under the contract.
- 1.25 "Written" or "in writing" means handwritten in ink or any form of electronic or mechanical writing.
- 2. Application

2.1

- These general conditions are applicable to all bids, contracts and orders including bids for functional and professional services, sales, hiring, letting and the granting or acquiring of immovable property, unless otherwise indicated in the bidding documents.
- Where applicable, special conditions of contract are also laid down to cover specific supplies, services or works.
- 2.3 Where such special conditions of contract are in conflict with these general conditions, the special conditions shall apply.
- 3. General
- 3.1 Unless otherwise indicated in the bidding documents, the purchaser

shall not be liable for any expense incurred in the preparation and submission of a bid. Where applicable a non-refundable fee for documents may be charged.

- 3.2 With certain exceptions, invitations to bid are only published in the Government Tender Bulletin. The Government Tender Bulletin may be obtained directly from the Government Printer, Private Bag X85, Pretoria 0001, or accessed electronically from www.treasury.gov.za
- 4. Standards

 4.1 The goods supplied shall conform to the standards mentioned in the bidding documents and Terms of Reference.

DRAFTED BY:	SIGNATURE DAT	E /
RECOMMENDED BY	19/14	408/17
REVIEWED BY:		PAPA
APPROVED BY BSC CHAIRPERSON	(M) GG AVIC 12	109/201
ADVERT APPROVED BY:		409 CC

5. Use of Contract documents and information; inspection.

- 5.1 The supplier shall not, without the purchaser's prior written consent, disclose the contract, or any provision thereof, or any Terms of Reference, plan, drawing, pattern, sample, or information furnished by or on behalf of the purchaser in connection therewith, to any person other than a person employed by the supplier in the performance of the contract. Disclosure to any such employed person shall be made in confidence and shall extend only so far as may be necessary for purposes of such performance.
- 5.2 The supplier shall not, without the purchaser's prior written consent, make use of any document or information mentioned in GCC clause 5.1 except for purposes of performing the contract.
- 5.3 Any document, other than the contract itself mentioned in GCC clause. 5.1 shall remain the property of the purchaser and shall be returned (all copies) to the purchaser on completion of the supplier's performance under the contract if so required by the purchaser.
- 5.4 The supplier shall permit the purchaser to inspect the supplier's records relating to the performance of the supplier and to have them audited by auditors appointed by the purchaser, if so required by the purchaser.
- 6. Patent rights 6.1

The supplier shall indemnify the purchaser against all third-party claims of infringement of patent, trademark, or industrial design rights arising from use of the goods or any part thereof by the purchaser.

7. Performance Security

- 7.1 Within thirty (30) days of receipt of the notification of contract award, the successful bidder shall furnish to the purchaser the performance security of the amount specified in SCC.
- 7.2 The proceeds of the performance security shall be payable to the purchaser as compensation for any loss resulting from the supplier's failure to complete his obligations under the contract.
- 7.3 The performance security shall be denominated in the currency of the contract, or in a freely convertible currency acceptable to the purchaser and shall be in one of the following forms:
 - a bank guarantee or an irrevocable letter of credit issued by a reputable bank located in the purchaser's country or abroad, acceptable to the purchaser, in the form provided in the bidding documents or another form acceptable to the purchaser; or
 - (b) a cashier's or certified cheque
- 7.4 The performance security will be discharged by the purchaser and returned to the supplier not later than thirty (30) days following the date of completion of the supplier's performance obligations under the contract, including any warranty obligations, unless otherwise specified in SCC.

8. Inspections, tests and analyses

8.1 All pre-bidding testing will be for the account of the bidder.

SCN

8.2 If it is a bid condition that supplies to be produced or services to be rendered should at any stage during production or execution or on completion be subject to inspection, the premises of the bidder or

38	cs of the bluder of	1
DRAFTED BY:	SIGNATURE	DATE 12 / DO / DO
RECOMMENDED BY		12/0/16
REVIEWED BY:	Me assessor	12/09/2019
APPROVED BY BSC CHAIRPERSON	fly had s	12 08 7018
ADVERT APPROVED BY:		12/04/201
IU3-19/20-0268-NMA		112 311 201

contractor shall be open, at all reasonable hours, for inspection by a representative of the Department or an organization acting on behalf of the Department.

- 8.3 If there are no inspection requirements indicated in the bidding documents and no mention is made in the contract, but during the contract period it is decided that inspections shall be carried out, the purchaser shall itself make the necessary arrangements, including payment arrangements with the testing authority concerned.
- 8.4 If the inspections, tests and analyses referred to in clauses 8.2 and 8.3 show the supplies to be in accordance with the contract requirements, the cost of the inspections, tests and analyses shall be defrayed by the purchaser.
- 8.5 Where the supplies or services referred to in clauses 8.2 and 8.3 do not comply with the contract requirements, irrespective of whether such supplies or services are accepted or not, the cost in connection with these inspections, tests or analyses shall be defrayed by the supplier.
- 8.6 Supplies and services which are referred to in clauses 8.2 and 8.3 and which do not comply with the contract requirements may be rejected.
- 8.7 Any contract supplies may on or after delivery be inspected, tested or analyzed and may be rejected if found not to comply with the requirements of the contract. Such rejected supplies shall be held at the cost and risk of the supplier who shall, when called upon, remove them immediately at his own cost and forthwith substitute them with supplies which do comply with the requirements of the contract. Failing such removal the rejected supplies shall be returned at the suppliers cost and risk. Should the supplier fail to provide the substitute supplies forthwith, the purchaser may, without giving the supplier further opportunity to substitute the rejected supplies, purchase such supplies as may be necessary at the expense of the supplier.
- 8.8 The provisions of clauses 8.4 to 8.7 shall not prejudice the right of the purchaser to cancel the contract on account of a breach of the conditions thereof, or to act in terms of Clause 23 of GCC.
- 9.1 The supplier shall provide such packing of the goods as is required to prevent their damage or deterioration during transit to their final destination, as indicated in the contract. The packing shall be sufficient to withstand, without limitation, rough handling during transit and exposure to extreme temperatures, salt and precipitation during transit, and open storage. Packing, case size and weights shall take into consideration, where appropriate, the remoteness of the goods' final destination and the absence of heavy handling facilities at all points in transit.
 - 9.2 The packing, marking, and documentation within and outside the packages shall comply strictly with such special requirements as shall be expressly provided for in the contract, including additional requirements, if any, specified in SCC, and in any subsequent instructions ordered by the purchaser.

10. Delivery and documents

- Delivery of the goods shall be made by the supplier in accordance with the terms specified in the contract. The details of shipping and/or other documents to be furnished by the supplier are specified in SCC.
- 10.2 Documents to be submitted by the supplier are specified in SCC.
- 11. Insurance 11.1 The goods supplied under the contract shall be fully insured in a freely convertible currency against loss or damage incidental to manufacture or acquisition, transportation, storage and delivery in the manner specified in the SCC.
- 12. Transportation

39	SIGNATI	JRE J	V	DATE	
DRAFTED BY:	Alst	100		17	1001
RECOMMENDED BY	1			1	> 61
REVIEWED BY:	XIII	and	DING	12	09/
APPROVED BY BSC CHAIRPERSON	The	Whoo	D	12	100
ADVERT APPROVED BY:) —	127	199 1

12.1 Should a price other than an all-inclusive delivered price be required, this shall be specified in the SCC.

13. Incidental Services

- 13.1 The supplier may be required to provide any or all of the following services, including additional services, if any, specified in SCC:
 - performance or supervision of on-site assembly and/or commissioning of the supplied goods;
 - (b) furnishing of tools required for assembly and/or maintenance of the supplied goods:
 - (c) furnishing of a detailed operations and maintenance manual for each appropriate unit of the supplied goods;
 - (d) performance or supervision or maintenance and/or repair of the supplied goods, for a period of time agreed by the parties, provided that this service shall not relieve the supplier of any warranty obligations under this contract; and
 - training of the purchaser's personnel, at the supplier's plant and/or on-site, in assembly, start-up, operation, maintenance, and/or repair of the supplied goods.
- Prices charged by the supplier for incidental services, if not included in the contract price for the goods, shall be agreed upon in advance by the parties and shall not exceed the prevailing rates charged to other parties by the supplier for similar services.
- 14. Spare parts 14.1

As specified in SCC, the supplier may be required to provide any or all of the following materials, notifications, and information pertaining to spare parts manufactured or distributed by the supplier:

- (a) such spare parts as the purchaser may elect to purchase from the supplier, provided that this election shall not relieve the supplier of any warranty obligations under the contract; and
- (b) in the event of termination of production of the spare parts:
 - (i)Advance notification to the purchaser of the pending termination, in sufficient time to permit the purchaser to procure needed requirements; and
 - (ii) following such termination, furnishing at no cost to the purchaser, the blueprints, drawings, and Terms of Reference of the spare parts, if requested.
- **15. Warranty** 15.1

The supplier warrants that the goods supplied under the contract are new, unused, of the most recent or current models, and that they incorporate all recent improvements in design and materials unless provided otherwise in the contract. The supplier further warrants that all goods supplied under this contract shall have no defect, arising from design, materials, or workmanship (except when the design and/or material is required by the purchaser's Terms of Reference) or from any act or omission of the supplier, that may develop under normal use of the supplied goods in the conditions prevailing in the country of final destination.

- This warranty shall remain valid for twelve (12) months after the goods, or any portion thereof as the case may be, have been delivered to and accepted at the final destination indicated in the contract, or for eighteen (18) months after the date of shipment from the port or place of loading in the source country, whichever period concludes earlier, unless specified otherwise in SCC.
- 15.3 The purchaser shall promptly notify the supplier in writing of and claims arising under this warranty.
- 15.4 Upon receipt of such notice, the supplier shall, within the period specified in SCC and with all reasonable speed, repair or replace the defective goods or parts thereof, without costs to the purchaser.

	SIGNATURE/I/		DATE-	6
DRAFTED BY:	6hl	CLA		1201
RECOMMENDED BY	1			9/10/
REVIEWED BY:	IIII G	Plan	12/	001 600
APPROVED BY BSC CHAIRPERSON	Mu M	العارية	12	08/7
ADVERT APPROVED BY:			10	20/20

- 15.5 If the supplier, having been notified, fails to remedy the defect(s) within the period specified in SCC, the purchaser may proceed to take such remedial action as may be necessary, at the supplier's risk and expense and without prejudice to any other rights which the purchaser may have against the supplier under the contract.
- **16. Payment** 16.1 The method and conditions of payment to be made to the supplier under this contract shall be specified in SCC.
 - The supplier shall furnish the purchaser with an invoice accompanied by a copy of the delivery note and upon fulfillment of other obligations stipulated in the contract.
 - Payments shall be made promptly by the purchaser, but in no case later than thirty (30) days after submission of an invoice or claim by the supplier.
 - 16.4 Payment will be made in Rand unless otherwise stipulated in SCC.
- 17.1 Prices charged by the supplier for goods delivered and services performed under the contract shall not vary from the prices quoted by the supplier in his bid, with the exception of any price adjustments authorized in SCC or in the purchaser's request for bid validity extension, as the case may be.
- Amendments 18.1 No variation in or modification of the terms of the contract shall be made except by written amendment signed by the parties concerned.
- 19. Assignment 19.1 The supplier shall not assign, in whole or in part, its obligations to perform under the contract, except with the purchaser's prior written consent.
- 20. Subcontracts 20.1 The supplier shall notify the purchaser in writing of all subcontracts awarded under this contracts if not already specified in the bid. Such notification, in the original bid or later, shall not relieve the supplier from any liability or obligation under the contract.

21. Delays in the supplier's performance

18. Contract

- 21.1 Delivery of the goods and performance of services shall be made by the supplier in accordance with the time schedule prescribed by the purchaser in the contract.
- 21.2 If at any time during performance of the contract, the supplier or its subcontractor(s) should encounter conditions impeding timely delivery of the goods and performance of services, the supplier shall promptly notify the purchaser in writing of the fact of the delay, its likely duration and its cause(s). As soon as practicable after receipt of the supplier's notice, the purchaser shall evaluate the situation and may at his discretion extend the supplier's time for performance, with or without the imposition of penalties, in which case the extension shall be ratified by the parties by amendment of contract.
- 21.3 No provision in a contract shall be deemed to prohibit the obtaining of supplies or services from a national department, provincial department, or a local authority.
- 21.4 The right is reserved to procure outside of the contract small quantities or to have minor essential services executed if an emergency arises, the supplier's point of supply is not situated at or near the place where the supplies are required, or the supplier's services are not readily available.
- 21.5 Except as provided under GCC Clause 25, a delay by the supplier in the performance of its delivery obligations shall render the supplier liable to the imposition of penalties, pursuant to GCC Clause 22, unless an extension of time is agreed upon pursuant to GCC Clause

21.2 without the application of penalties.

on or penalties.	Λ
41	// a
	SIGNATURE DATE
DRAFTED BY:	Met 1000 14
RECOMMENDED BY	Valenta
REVIEWED BY:	W. 4 2 12 12 19/2019
APPROVED BY BSC CHAIRPERSON	12 04 601
ADVERT APPROVED BY:	120 9 120
MU3-19/20-0268-NMA	

21.6 Upon any delay beyond the delivery period in the case of a supplies contract, the purchaser shall, without canceling the contract, be entitled to purchase supplies of a similar quality and up to the same quantity in substitution of the goods not supplied in conformity with the contract and to return any goods delivered later at the supplier's expense and risk, or to cancel the contract and buy such goods as may be required to complete the contract and without prejudice to his other rights, be entitled to claim damages from the supplier.

22. Penalties

22.1

Subject to GCC Clause 25, if the supplier fails to deliver any or all of the goods or to perform the services within the period(s) specified in the contract, the purchaser shall, without prejudice to its other remedies under the contract, deduct from the contract price, as a penalty, a sum calculated on the delivered price of the delayed goods or unperformed services using the current prime interest rate calculated for each day of the delay until actual delivery or performance. The purchaser may also consider termination of the contract pursuant to GCC Clause 23.

23. Termination for default

23.1 The purchaser, without prejudice to any other remedy for breach of contract, by written notice of default sent to the supplier, may terminate this contract in whole or in part:

- if the supplier fails to deliver any or all of the goods within the period(s) specified in the contract, or within any extension thereof granted by the purchaser pursuant to GCC Clause 21.2;
- (b) if the Supplier fails to perform any other obligation(s) under the contract; or
- (c) if the supplier, in the judgment of the purchaser, has engaged in corrupt or fraudulent practices in competing for or in executing the contract.
- 23.2 In the event the purchaser terminates the contract in whole or in part, the purchaser may procure, upon such terms and in such manner as it deems appropriate, goods, works or services similar to those undelivered, and the supplier shall be liable to the purchaser for any excess costs for such similar goods, works or services. However, the supplier shall continue performance of the contract to the extent not terminated.

24. Anti-dumping and countervailing duties and rights

When, after the date of bid, provisional payments are required, or antidumping or countervailing duties are imposed, or the amount of a provisional payment or anti-dumping or countervailing right is increased in respect of any dumped or subsidized import, the State is not liable for any amount so required or imposed, or for the amount of any such increase. When, after the said date, such a provisional payment is no longer required or any such antidumping or countervailing right is abolished, or where the amount of such provisional payment or any such right is reduced, any such favourable difference shall on demand be paid forthwith by the contractor to the State or the State may deduct such amounts from moneys (if any) which may otherwise be due to the contractor in regard to supplies or services which he delivered or rendered, or is to deliver or render in terms of the contract or any other contract or any other amount which may be due to him

25. Force Majeure 25.1

Notwithstanding the provisions of GCC Clauses 22 and 23, the supplier shall not be liable for forfeiture of its performance security, damages, or termination for default if and to the extent that his delay in performance or other failure to perform his obligations under the contract is the result of an event of force majeure.

25.2 If a force majeure situation arises, the supplier shall promptly notify the purchaser in writing of such condition and the cause thereof. Unless otherwise directed by the purchaser in writing, the supplier

42	1			
	SIGNATURE/	1	DATE	. 1
DRAFTED BY:	Roly &	A Land	120	9/1
RECOMMENDED BY	1		1>40	Va
REVIEWED BY:	1116.6	Maya	12/10	1/2
APPROVED BY BSC CHAIRPERSON	Jul he	Redd	12/10	170
ADVERT APPROVED BY:			12409	VID.
U3-19/20-0268-NMA	100		11.	1

shall continue to perform its obligations under the contract as far as is reasonably practical, and shall seek all reasonable alternative means for performance not prevented by the force majeure event.

26. Termination for insolvency

26.1 The purchaser may at any time terminate the contract by giving written notice to the supplier if the supplier becomes bankrupt or otherwise insolvent. In this event, termination will be without compensation to the supplier, provided that such termination will not prejudice or affect any right of action or remedy which has accrued or will accrue thereafter to the purchaser.

27. Settlement of Disputes

- 27.1 If any dispute or difference of any kind whatsoever arises between the purchaser and the supplier in connection with or arising out of the contract, the parties shall make every effort to resolve amicably such dispute or difference by mutual consultation.
- 27.2 If, after thirty (30) days, the parties have failed to resolve their dispute or difference by such mutual consultation, then either the purchaser or the supplier may give notice to the other party of his intention to commence with mediation. No mediation in respect of this matter may be commenced unless such notice is given to the other party.
- 27.3 Should it not be possible to settle a dispute by means of mediation, it may be settled in a South African court of law.
- 27.4 Mediation proceedings shall be conducted in accordance with the rules of procedure specified in the SCC.
- 27.5 Notwithstanding any reference to mediation and/or court proceedings herein,
 - (a) the parties shall continue to perform their respective obligations under the contract unless they otherwise agree; and
 - (b) the purchaser shall pay the supplier any monies due the supplier.
- 28.1 Except in cases of criminal negligence or willful misconduct, and in the case of infringement pursuant to Clause 6;
 - (a) the supplier shall not be liable to the purchaser, whether in contract, tort, or otherwise, for any indirect or consequential loss or damage, loss of use, loss of production, or loss of profits or interest costs, provided that this exclusion shall not apply to any obligation of the supplier to pay penalties and/or damages to the purchaser; and
 - (b) the aggregate liability of the supplier to the purchaser, whether under the contract, in tort or otherwise, shall not exceed the total contract price, provided that this limitation shall not apply to the cost of repairing or replacing defective equipment.

29. Governing Language 29.1

The contract shall be written in English. All correspondence and other documents pertaining to the contract that is exchanged by the parties shall also be written in English.

30. Applicable Law

30.1

The contract shall be interpreted in accordance with South African laws, unless otherwise specified in SCC.

31. Notices

31.1 Every written acceptance of a bid shall be posted to the supplier concerned by registered or certified mail and any other notice to him shall be posted by ordinary mail to the address furnished in his bid or to the address notified later by him in writing and such posting shall be deemed to be proper service of such notice

The time mentioned in the contract documents for performing any act after such aforesaid notice has been given, shall be reckoned from the date of posting of such notice.

32. Taxes and Duties

32.1 A foreign supplier shall be entirely responsible for all taxes, stamp

43	SIGNATURE	AM	DATE	
DRAFTED BY:	Culil	of the	17/6	26/180
RECOMMENDED BY	Hay		1/3	AIL
REVIEWED BY:	Villa	1 0 00 CO	7 12	
APPROVED BY BSC CHAIRPERSON	The x		1 /2/	09/20
ADVERT APPROVED BY:	1		101	0
U3-19/20-0268-NMA			120	1/201

duties, license fees, and other such levies imposed outside the purchaser's country.

- 32.2 A local supplier shall be entirely responsible for all taxes, duties, license fees, etc., incurred until delivery of the contracted goods to the purchaser.
- 32.3 No contract shall be concluded with any bidder whose tax matters are not in order. Prior to the award of a bid the Department must be in possession of a tax clearance certificate, submitted by the bidder.

This certificate must be an original issued by the South African Revenue Services.

44	SIGNATURE /	1	DATE	1	,
DRAFTED BY:	Mul	Carl 1	An	160	1,8
RECOMMENDED BY			1/3	3/	/ X ,
REVIEWED BY:	VIIIV	The Report	3 (2	100	1
APPROVED BY BSC CHAIRPERSON	The the	Text.	12	loe/	13
ADVERT APPROVED BY:)	12	00	0

Part 5 – Schedule B Application for Tax Clearance Certificate

CSD VERIFICATION /TAX COMPLIANCE REQUIREMENTS

IT IS A CONDITION OF BIDDING:-

 The Department of Health will verify the tax compliance status of bidders on the central Supplier Database (CSD) for all price quotations and competitive bids exceeding the value of R30 000 (Vat inclusive) prior to award as per National Treasury Instruction no 4A of 2016/17 Central Supplier Database.

45	\$IGNATURE DATE O
DRAFTED BY:	X11/109/19
RECOMMENDED BY	
REVIEWED BY:	MICO 1 DE 100 100 100 100
APPROVED BY BSC CHAIRPERSON	W/ 12 12 12 12 12 12 12 12 12 12 12 12 12
ADVERT APPROVED BY:	12 39/00

Pricing Schedule

ANNEXURE 1: MACHINE 1: CONTINUOUS RENAL REPLACEMENT THERAPY MACHINE (CRRT): OPTION 1: OUTRIGHT PURCHASE PRICING SCHEDULE

i. Please complete the table below to enable price evaluations:

Description	1st year Price incl. VAT	2nd year Price incl. VAT	3rd year Price incl. VAT
Renal CRRT machine			
Comprehensive 5 Year			
maintenance plan (year 3 to year			
7)			
Second 5 year comprehensive			
maintenance plan (year 8 to year			
12)			
Consumables		No.	
1 x CRRT set (list and include all			
consumables except fluids			
required to run a 24 CVVHDF for			
1 patient			
Bicarbonate buffered		V-2-2-3-3-3-3-3-3-3-3-3-3-3-3-3-3-3-3-3-	
haemofiltration solution in 5L			
bag.			
Cost of consumables for 1			
plasma exchange for 1			
patient (including all			
consumables and			
filters, except			
replacement solution)			

ANNEXURE 2: MACHINE 1 - ADDITIONAL OPTIONS

No	Component	Qty.	Part No.	Year 1 Price Excludi ng VAT	Year 2 Price Excludi ng VAT	Year 3 Price Excluding VAT
(IIII biology)						
	SUB TOTAL					
	ADD 14% VAT					29
	TOTAL					

NOTE: This should not form part of the final offer. The purchaser reserves the right to select the required items.

46	
DRAFTED BY:	SIGNATURE DATE
RECOMMENDED BY	The state of the s
REVIEWED BY:	11 (12 846 12 10912016
APPROVED BY BSC CHAIRPERSON	12 , e 12
ADVERT APPROVED BY:	12/2/2013
10/20 0260 NIMA	1 477 (-1)

SCMU3-19/20-0268-NMA

MACHINE 1: CONTINUOUS RENAL REPLACEMENT THERAPY MACHINE (CRRT): OPTION 2: LEASE

Description	1 st year Lease amount (incl. VAT) per month	2nd year Lease amount (incl. VAT) per month	3rd year Lease amount (incl. VAT) per month
Complete CRRT machine			
Consumables			
1 x CRRT set (list and include all consumables except fluids required to run a 24 CVVHDF for 1 patient.			
Bicarbonate buffered haemofiltration solution in 5L bag.			
Cost of consumables for 1 plasma exchange for 1 patient (including all consumables and filters, except replacement solution)			

ANNEXURE 2: MACHINE 1 - ADDITIONAL OPTIONS

No	Component	Qty.	Part No.	1st year Lease amount (incl. VAT) per month	2nd year Lease amount (incl. VAT) per month	3rd year Lease amount (incl. VAT) per month
	SUB TOTAL					
	ADD 14% VAT					
	TOTAL					

NOTE: The suppliers takes full responsibility in the lease option (supply, delivery, installation, commissioning, maintenance and supply of consumables, accessories and spare parts.

	SIGNATURE DATE
DRAFTED BY:	hlula 12800 /1
RECOMMENDED BY	HI DE
REVIEWED BY:	11/11 Color 12/19/19
APPROVED BY BSC CHAIRPERSON	14 1900 17 60
ADVERT APPROVED BY:	12

ANNEXURE 4: MACHINE 2: SINGLE PUMP INTERMITTENT HAEMODIALYSIS MACHINE: OPTION 1: OUTRIGHT PURCHASE PRICING SCHEDULE

Description	1 st year Price incl. VAT	2 nd year Price incl. VAT	3rd year Price incl. VAT
Single pump intermittent haemodialysis machines			
Double pump intermittent hemodialysis machines			
5 Year maintenance plan			
Consumables			
Dialyzers			
Blood line			
Fistula needle			
Disinfectant			
Concentrate (Haemocarb and bicarb)			
Heparin syringes			

ANNEXURE 5: MACHINE 2 - ADDITIONAL OPTIONS

No	Component	Qty.	Part No.	1st year Lease amount (incl. VAT) per month	2nd year Lease amount (incl. VAT) per month	3rd year Lease amount (incl. VAT) per month
	SUB TOTAL					
	ADD 14% VAT					
	TOTAL					

NOTE: This should not form part of the final offer. The purchaser reserves the right to select the required items.

48	SIGNATURE DATE
DRAFTED BY:	SIGNATURE DATE
RECOMMENDED BY	12 12
REVIEWED BY:	My ang 15,086
APPROVED BY BSC CHAIRPERSON	M / 12/100/
ADVERT APPROVED BY:	1 Double

ANNEXURE 6: MACHINE 2: SINGLE PUMP INTERMITTENT HAEMODIALYSIS MACHINE: OPTION 2: LEASE

Description	1 st year Price incl. VAT	2 nd year Price incl. VAT	3rd year Price incl. VAT
Single pump intermittent			
haemodialysis machines			
Double pump intermittent			
hemodialysis machines			
5 Year maintenance plan			
Consumables			
Dialyzers			
Blood line			
Fistula needle			
Disinfectant			
Concentrate (Haemocarb and bicarb)			
Heparin syringes			
-			

ANNEXURE 7: MACHINE 12 - ADDITIONAL OPTIONS

Component	Qty.	Part No.	1st year Lease amount (incl. VAT) per month	2nd year Lease amount (incl. VAT) per month	3rd year Lease amount (incl. VAT) per month
SUB TOTAL					
ADD 14% VAT					
TOTAL					
	SUB TOTAL ADD 14% VAT	SUB TOTAL ADD 14% VAT	SUB TOTAL ADD 14% VAT	Component Qty. Part (incl. VAT) per month SUB TOTAL ADD 14% VAT	Component Qty. Part Lease amount (incl. VAT) per month Per month SUB TOTAL ADD 14% VAT

NOTE: The suppliers takes full responsibility in the lease option (supply, delivery, installation, commissioning, maintenance and supply of consumables, accessories and spare parts

	SIGNATURE DATE
DRAFTED BY:	My 17/09/
RECOMMENDED BY	A SPIN
REVIEWED BY:	11/1 Que 12/19/12
APPROVED BY BSC CHAIRPERSON	1 2 ng
ADVERT APPROVED BY:	10 /13/26

Part 5 – Schedule D Declaration of Interest

SBD 4

DECLARATION OF INTEREST

- 1. Any legal person, including persons employed by the state¹, or persons having a kinship with persons employed by the state, including a blood relationship, may make an offer or offers in terms of this invitation to bid (includes an advertised competitive bid, a limited bid, a proposal or written price quotation). In view of possible allegations of favouritism, should the resulting bid, or part thereof, be awarded to persons employed by the state, or to persons connected with or related to them, it is required that the bidder or his/her authorised representative declare his/her position in relation to the evaluating/adjudicating authority where-
 - the bidder is employed by the state; and/or
 - the legal person on whose behalf the bidding document is signed, has a relationship with persons/a person who are/is involved in the evaluation and or adjudication of the bid(s), or where it is known that such a relationship exists between the person or persons for or on whose behalf the declarant acts and persons who are involved with the evaluation and or adjudication of the bid.

2.	In order to give effect to the above, the following questionnaire must be completed and submitted with the bid.
2.1	Full Name of bidder or his or her representative:
2.2	Identity Number:
2.3	Position occupied in the Company (director, trustee, shareholder², member):
2.4	
2.5	Registration number of company, enterprise, close corporation, partnership agreement or trust:
2.6	Tax Reference Number:
2.7	VAT Registration Number:
2.6.1	The names of all directors / trustees / shareholders / members, their individual identity numbers, tax reference numbers and, if applicable, employee / PERSAL numbers must be indicated in paragraph 3 below.
"State" me	
	 (a) any national or provincial department, national or provincial public entity or constitutional institution within the meaning of the Public Finance Management Act, 1999 (Act No. 1 of 1999); (b) any municipality or municipal entity; (c) provincial legislature; (d) national Assembly or the national Council of provinces; or (e) Parliament.

²"Shareholder" means a person who owns shares in the company and is actively involved in the management of the enterprise or business and exercises control over the enterprise.

2.7	Are you or any person connected with	the bidder	YES /NO	
		50 DRAFTED BY:	SIGNATURE	DATE
		RECOMMENDED BY		1 (198/10)
		REVIEWED BY:	Ml awaya	12/69/R019
		APPROVED BY BSC CHAIRPERSON	my whose	12/09/70/
	SCMU3	-19/20-0268-NMA		12/09/2019

		presently employed by the state?				
	2.7.1	If so, furnish the following particulars:				
		Name of person / director / trustee / share	reholder/ member:			
		Name of state institution at which you or connected to the bidder is employed :	the person			
		Position occupied in the state institution:				
		Any other particulars:				
	2.7.2	If you are presently employed by the stat the appropriate authority to undertake re- work outside employment in the public se	munerative		YES / NO	
	2.7.2.1	If yes, did you attach proof of such autho document?	rity to the bid		YES / NO	
		(Note: Failure to submit proof of such aut applicable, may result in the disqualification	thority, where on of the bid.			
	2.7.2.2	If no, furnish reasons for non-submission	of such proof:			
	2.8	oid you or your spouse, or any of the comp trustees / shareholders / members or the business with the state in the previous tw	ir spouses conduct		YES / NO	
	2.8.1	If so, furnish particulars:				
	2.9	Do you, or any person connected with the any relationship (family, friend, other) with employed by the state and who may be in the evaluation and or adjudication of this	n a person Ivolved with		YES / NO	
	2.9.1	If so, furnish particulars.	oid:			
2.10	awar any d who	rou, or any person connected with the bidde e of any relationship (family, friend, other) other bidder and any person employed by may be involved with the evaluation and o s bid?	between the state	YES/NO		
2.10.1	If so, furn	nish particulars.				
			51	SIGNA	TUDE	T p. ==
		DR	AFTED BY:	/ Not	ISL STATE OF THE PARTY OF THE P	DATE
		RE	COMMENDED BY	W.	THE	1799

SCMU3-19/20-0268-NMA

REVIEWED BY:

APPROVED BY BSC CHAIRPERSON

ADVERT APPROVED BY:

11	Do you or any of the direct of the company have any in whether or not they are bid	nterest in any other related	rs / members YES/NO d companies	
11.1	If so, furnish particulars:			
F	Full details of directors / tru	ustees / members / share	Personal Income Tax	State Employee
			Reference Number	Number / Persal Number
-				
F				
L				
0	4 DECLARATION			
	CERTIFY THAT THE I ACCEPT THAT THE	INFORMATION FURNIS STATE MAY REJECT	HED IN PARAGRAPHS 2 an THE BID OR ACT AGA	d 3 ABOVE IS CORRECT. INST ME SHOULD THIS
	DECLARATION PROVE	TO BE FALSE.		
	Signature		Date	
	Position		••••••	

52	AN	
DRAFTED BY:	SIGNATURE /	DATE / 08/10
RECOMMENDED BY		12 1
REVIEWED BY:	Musana	12/29/12/19
APPROVED BY BSC CHAIRPERSON	Wheav	200 701
ADVERT APPROVED BY:	CA	12/0/2 /20/
SCMU3-19/20-0268-NMA		1 1

Declaration of Bidder's Past Supply Chain Management Practices

SBD 8

DECLARATION OF BIDDER'S PAST SUPPLY CHAIN MANAGEMENT PRACTICES

- 1 This Standard Bidding Document must form part of all bids invited.
- 2 It serves as a declaration to be used by institutions in ensuring that when goods and services are being procured, all reasonable steps are taken to combat the abuse of the supply chain management system.
- 3 The bid of any bidder may be disregarded if that bidder, or any of its directors have
 - a. abused the institution's supply chain management system;
 - b. committed fraud or any other improper conduct in relation to such system; or
 - c. failed to perform on any previous contract.
- In order to give effect to the above, the following questionnaire must be completed and submitted with the bid.

Item	Question	Yes	No
4.1	Is the bidder or any of its directors listed on the National Treasury's database as companies or persons prohibited from doing business with the public sector?	Yes	No
	(Companies or persons who are listed on this database were informed in writing of		
	this restriction by the National Treasury after the audi alteram partem rule was		
	applied).		
4.1.1	If so, furnish particulars:		
4.2	Is the bidder or any of its directors listed on the Register for Tender Defaulters in terms of section 29 of the Prevention and Combating of Corrupt Activities Act (No 12 of 2004)? To access this Register enter the National Treasury's website, www.treasury.gov.za, click on the icon "Register for Tender Defaulters" or	Yes	No 🔲
	submit your written request for a hard copy of the Register to facsimile number (012) 3265445.		
4.2.1	If so, furnish particulars:		
4.3	Was the bidder or any of its directors convicted by a court of law (including a court outside of the Republic of South Africa) for fraud or corruption during the past five years?	Yes	No
4.3.1	If so, furnish particulars:		
4.4	Was any contract between the bidder and any organ of state terminated during the past five years on account of failure to perform on or comply with the contract?	Yes	No

53	SIGNATURE DATE
DRAFTED BY:	My 100/100/
RECOMMENDED BY	
REVIEWED BY:	1110 Que 12109N
APPROVED BY BSC CHAIRPERSON	N 14 12 09 1
ADVERT APPROVED BY:	209/2

4.4.1	it so, turnish particulars:		
CERT	TIFICATION		
I, THE	UNDERSIGNED (FULL NAME)		
	IFY THAT THE INFORMATION FURNISHED OF RRECT.	I THIS DECLARATION FORM IS TRUE AI	٧D
	CEPT THAT, IN ADDITION TO CANCELLATION AINST ME SHOULD THIS DECLARATION PROVE		ΞN
AUA	THE SHOOLD THIS DECLARATION FROVE	TO BE TALSE.	
Sign	nature	Date	
Positio	on	Name of Bidder	

Part 5 – Schedule F CERTIFICATE OF INDEPENDENT BID DETERMINATION

- 1 This Standard Bidding Document (SBD) must form part of all bids¹ invited.
- Section 4 (1) (b) (iii) of the Competition Act No. 89 of 1998, as amended, prohibits an agreement between, or concerted practice by, firms, or a decision by an association of firms, if it is between parties in a horizontal relationship and if it involves collusive bidding (or bid rigging).² Collusive bidding is a *pe se* prohibition meaning that it cannot be justified under any grounds.
- Treasury Regulation 16A9 prescribes that accounting officers and accounting authorities must take all reasonable steps to prevent abuse of the supply chain management system and authorizes accounting officers and accounting authorities to:
 - a. disregard the bid of any bidder if that bidder, or any of its directors have abused the institution's supply chain management system and or committed fraud or any other improper conduct in relation to such system.
 - b. cancel a contract awarded to a supplier of goods and services if the supplier committed any corrupt or fraudulent act during the bidding process or the execution of that contract.
- This SBD serves as a certificate of declaration that would be used by institutions to ensure that, when bids are considered, reasonable steps are taken to prevent any form of bid-rigging.
- In order to give effect to the above, the attached Certificate of Bid Determination (SBD 9) must be completed and submitted with the bid:
- ¹ Includes price quotations, advertised competitive bids, limited bids and proposals.
- ² Bid rigging (or collusive bidding) occurs when businesses, that would otherwise be expected to compete, secretly conspire to raise prices or lower the quality of goods and / or services for purchasers who wish to acquire goods and / or services through a bidding process. Bid rigging is, therefore, an agreement between competitors not to compete.

	55	1	1	1		
	DRAFTED BY:	SIGNATURE			DATE	9/10
	RECOMMENDED BY	The state of the s	THE	-	1/3	411/2
	REVIEWED BY:	Note (5)	Way	na	12/00	1 bole
	APPROVED BY BSC CHAIRPERSON	THE P	Res	20	12	67-K
	ADVERT APPROVED BY:	10		,	2/10	12018
SCMU3	3-19/20-0268-NMA	1000	/		1-10	1001)

CERTIFICATE OF INDEPENDENT BID DETERMINATION

, the undersigned, in submitting the accompanying bid:	
Bid Number and Description)	
n response to the invitation for the bid made by:	
Name of Institution)	-
do hereby make the following statements that I certify to be true and complete in every resp	ect:
certify, on behalf of:tr	nat:

- 1. I have read and I understand the contents of this Certificate;
- 2. I understand that the accompanying bid will be disqualified if this Certificate is found not to be true and complete in every respect;
- 3. I am authorized by the bidder to sign this Certificate, and to submit the accompanying bid, on behalf of the bidder;
- 4. Each person whose signature appears on the accompanying bid has been authorized by the bidder to determine the terms of, and to sign the bid, on behalf of the bidder;
- 5. For the purposes of this Certificate and the accompanying bid, I understand that the word "competitor" shall include any individual or organization, other than the bidder, whether or not affiliated with the bidder, who:
 - (a) has been requested to submit a bid in response to this bid invitation;
 - could potentially submit a bid in response to this bid invitation, based on their qualifications, abilities or experience; and
 - (c) provides the same goods and services as the bidder and/or is in the same line of business as the bidder
- 6. The bidder has arrived at the accompanying bid independently from, and without consultation, communication, agreement or arrangement with any competitor. However communication between partners in a joint venture or consortium³ will not be construed as collusive bidding.
- 7. In particular, without limiting the generality of paragraphs 6 above, there has been no consultation, communication, agreement or arrangement with any competitor regarding:
 - (a) prices;
 - (b) geographical area where product or service will be rendered (market allocation)
 - (c) methods, factors or formulas used to calculate prices;
 - (d) the intention or decision to submit or not to submit, a bid;

	SIGNATURE	DATE A A
DRAFTED BY:	My South	17/09/1
RECOMMENDED BY		12/11/1
REVIEWED BY:	Miller ava	12/09/07
APPROVED BY BSC CHAIRPERSON	he he had	209/7
ADVERT APPROVED BY:		12/09/20

- (e) the submission of a bid which does not meet the specifications and conditions of the bid; or
- (f) bidding with the intention not to win the bid.
- 8. In addition, there have been no consultations, communications, agreements or arrangements with any competitor regarding the quality, quantity, specifications and conditions or delivery particulars of the products or services to which this bid invitation relates.
- The terms of the accompanying bid have not been, and will not be, disclosed by the bidder, directly or indirectly, to any competitor, prior to the date and time of the official bid opening or of the awarding of the contract.
- ³ Joint venture or Consortium means an association of persons for the purpose of combining their expertise, property, capital, efforts, skill and knowledge in an activity for the execution of a contract.
 - 10. I am aware that, in addition and without prejudice to any other remedy provided to combat any restrictive practices related to bids and contracts, bids that are suspicious will be reported to the Competition Commission for investigation and possible imposition of administrative penalties in terms of section 59 of the Competition Act No 89 of 1998 and or may be reported to the National Prosecuting Authority (NPA) for criminal investigation and or may be restricted from conducting business with the public sector for a period not exceeding ten (10) years in terms of the Prevention and Combating of Corrupt Activities Act No 12 of 2004 or any other applicable legislation.

Signature	Date			
Position Name of Bidder				
Part 5 – Schedule G				
Qualifications and Experience Details of the extent of the bidders activities and business, e.g. branches etc:				

2.

Description of Contract Contact Contact Contact Alue Person Number

Start End Date date

A list of existing /previous contracts relating to services which are similar to the Services:

DRAFTED BY:

RECOMMENDED BY

REVIEWED BY:

APPROVED BY BSC CHAIRPERSON

ADVERT APPROVED BY:

SCMU3-19/20-0268-NMA

		4100					
3.	The number of yea materially the same	rs that the as the Sen	bidder has vices:	been in the busine	ess of providing se	ervices which are	
4.	The name of the pe	rson who st	nall manage	the Services:			
5.	Detail such person's qualifications and experience below :						
			 Sid	GNATURE OF (ON	I BEHALF OF) BII	 DDER	
nrese	nce of :		 NA	ME IN CAPITALS			
•••••			•••				
•••••			•••				

DRAFTED BY: RECOMMENDED BY REVIEWED BY: APPROVED BY BSC CHAIRPERSON ADVERT APPROVED BY:

SCMU3-19/20-0268-NMA

Part 5 - Schedule H

Organisation type

PARTNERSHIP/CLOSED CORPORATION/COMPANY (delete which is not applicable) rises of the following partners/members/directors:

				y	partitoi	o/momb	ers/direc	1013.			
	1.	NAME									
		ADDRESS	:								
		ID NUMBER	₹:			-					
	2.	NAME	:								_
		ADDRESS	:								<u></u>
		ID NUMBER	₹:								
	3.	NAME	:								_
		ADDRESS	ï								
		ID NUMBER	l:								-
	4.	NAME	:								
		ADDRESS	:								
		ID NUMBER	:								T.2
	5.	NAME	:								
		ADDRESS	:								
		ID NUMBER	:								14
					 S	SIGNAT	URE OF	(ON BEH	ALF O	F) BIDD	ER
the p	oreser	nce of :			 N	IAME IN	CAPITA	ALS	••••••	••••••	••••••
						chedule					
				Orgar	nisation	nal struc	cture				

59	SIGNATURE
DRAFTED BY:	SIGNATURE DATE
RECOMMENDED BY	
REVIEWED BY:	11/1 (2) 2 1000
APPROVED BY BSC CHAIRPERSON	12/00/
ADVERT APPROVED BY:	112 1009

	SIGNATURE OF (ON BEHALF OF) BIDDER	
	NAME IN CAPITALS	
In the pr	resence of:	
m dio pi		
1		
2		
	Part 5 – Schedule J	
	Details of Supplier's Nearest Office	
1. Ph	nysical address of supplier's office	
1 Tel	lephone No of office:	
	DRAFTED BY:	.6
	RECOMMENDED BY	17
	REVIEWED BY:	7
	APPROVED BY BSC CHAIRPERSON DURAGE 12/09/12	0/9
	ADVERT APPROVED BY:	
	SCMU3-19/20-0268-NMA	17

3	Time period for which such office has been us	sed by supplier :
		SIGNATURE OF (ON BEHALF OF) BIDDER
		NAME IN CAPITALS
In the	e presence of :	
1.		
2.		

DRAFTED BY: RECOMMENDED BY REVIEWED BY: APPROVED BY BSC CHAIRPERSON ADVERT APPROVED BY:

SCMU3-19/20-0268-NMA

Part 5 - Schedule J Financial Particulars This schedule must be completed by the bidder and submitted together with the bid. Documentary proof confirming availability of financial resources to execute the contract from the bidder's financial institution and. If this requirement is not complied with in full the bid may be considered invalid. Nature of Service : _ Name of bidder: Bid Number: FINANCIAL POSITION OF BIDDER I/we hereby certify that I/we have the necessary financial capacity and resources to execute the above contract successfully for the bid amount. I / we hereby attach letter confirming availability of financial resources from the financial institution. I / we give the ECDOH permission to contact the financial institution below to confirm the information provided. In the absence of the above, a letter confirming that the bidder has applied for financial assistance from any financial institution and that the institution is willing to favourably consider such application in the event that the bidder is successful, will also satisfy the Department. NAME OF **FINANCIAL** INSTITUTION **ADDRESS** TEL.NO **FAX NO** CONTACT **PERSON** SIGNATURE OF (ON BEHALF OF) BIDDER NAME IN CAPITALS In the presence of: 1.

DRAFTED BY:

RECOMMENDED BY

REVIEWED BY:

APPROVED BY BSC CHAIRPERSON

ADVERT APPROVED BY:

SCMU3-19/20-0268-NMA

2.

Part 5 - Schedule K

SBD 6.1

PREFERENCE POINTS CLAIM FORM IN TERMS OF THE PREFERENTIAL PROCUREMENT REGULATIONS 2017

This preference form must form part of all bids invited. It contains general information and serves as a claim form for preference points for Broad-Based Black Economic Empowerment (B-BBEE) Status Level of Contribution

NB:

BEFORE COMPLETING THIS FORM, BIDDERS MUST STUDY THE GENERAL CONDITIONS, DEFINITIONS AND DIRECTIVES APPLICABLE IN RESPECT OF B-BBEE, AS PRESCRIBED IN THE PREFERENTIAL PROCUREMENT REGULATIONS, 2017.

1. GENERAL CONDITIONS

- 1.1 The following preference point systems are applicable to all bids:
 - the 80/20 system for requirements with a Rand value of up to R50 000 000 (all applicable taxes included); and
- 1.2 The value of this bid is estimated to exceed (all applicable taxes included) and therefore the 80/20.preference point system shall be applicable.
- 1.3 Preference points for this bid shall be awarded for:
 - (c) Price; and
 - (d) B-BBEE Status Level of Contribution.
- 1.4 The maximum points for this bid are allocated as follows:

	POINTS
PRICE	80
B-BBEE STATUS LEVEL OF CONTRIBUTION	20
Total points for Price and B-BBEE must not exceed	100

- 1.5 Failure on the part of a bidder to submit a B-BBEE Verification Certificate from a Verification Agency accredited by the South African Accreditation System (SANAS), or a Registered Auditor approved by the Independent Regulatory Board of Auditors (IRBA) or a sworn affidavit confirming annual turnover and level of black ownership in case of an EME and QSE together with the bid, will be interpreted to mean that preference points for B-BBEE status level of contribution are not claimed.
- 1.6 The purchaser reserves the right to require of a bidder, either before a bid is adjudicated or at any time subsequently, to substantiate any claim in regard to preferences, in any manner required by the purchaser.

2. DEFINITIONS

- (a) "all applicable taxes" includes value-added tax, pay as you earn, income tax, unemployment insurance fund contributions and skills development levies;
- (b) "B-BBEE" means broad-based black economic empowerment as defined in section 1 of the Broad-Based Black Economic Empowerment Act;
- (c) "B-BBEE status level of contributor" means the B-BBEE status received by a measured entity based on its overall performance using the relevant scorecard contained in the Codes of Good Practice on Black Economic Empowerment, issued in terms of section 9(1) of the Broad-Based Black Economic Empowerment Act;

IGNATURE DATE	2
16 04/1	\exists
1 1 1000 1000000	a
4 12 09 21	4
12/20/02	5//
	MATURE 12 12 12 12 12 12 12 12 12 12 12 12 12

- (d) "bid" means a written offer in a prescribed or stipulated form in response to an invitation by an organ of state for the provision of services, works or goods, through price quotations, advertised competitive bidding processes or proposals;
- (e) "Broad-Based Black Economic Empowerment Act" means the Broad-Based Black Economic Empowerment Act, 2003 (Act No. 53 of 2003);
- (f) "comparative price" means the price after the factors of a non-firm price and all unconditional discounts that can be utilized have been taken into consideration;
- (g) "consortium or joint venture" means an association of persons for the purpose of combining their expertise, property, capital, efforts, skill and knowledge in an activity for the execution of a contract;
- (h) "contract" means the agreement that results from the acceptance of a bid by an organ of state;
- (i) "EME" means an Exempted Micro Enterprise as defines by Codes of Good Practice under section 9 (1) of the Broad-Based Black Economic Empowerment Act, 2003 (Act No. 53 of 2003);
- (j) "Firm price" means the price that is only subject to adjustments in accordance with the actual increase or decrease resulting from the change, imposition, or abolition of customs or excise duty and any other duty, levy, or tax, which, in terms of the law or regulation, is binding on the contractor and demonstrably has an influence on the price of any supplies, or the rendering costs of any service, for the execution of the contract;
- (k) "functionality" means the measurement according to predetermined norms, as set out in the bid documents, of a service or commodity that is designed to be practical and useful, working or operating, taking into account, among other factors, the quality, reliability, viability and durability of a service and the technical capacity and ability of a bidder;
- (I) "non-firm prices" means all prices other than "firm" prices;
- (m) "person" includes a juristic person;
- "QSE" means a Qualifying Small Enterprise as defines by Codes of Good Practice under section 9 (1) of the Broad-Based Black Economic Empowerment Act, 2003 (Act No. 53 of 2003);
- (o) "rand value" means the total estimated value of a contract in South African currency, calculated at the time of bid invitations, and includes all applicable taxes and excise duties;
- (p) "sub-contract" means the primary contractor's assigning, leasing, making out work to, or employing, another person to support such primary contractor in the execution of part of a project in terms of the contract;
- (q) "total revenue" bears the same meaning assigned to this expression in the Codes of Good Practice on Black Economic Empowerment, issued in terms of section 9(1) of the Broad-Based Black Economic Empowerment Act and promulgated in the Government Gazette on 9 February 2007;
- (r) "trust" means the arrangement through which the property of one person is made over or bequeathed to a trustee to administer such property for the benefit of another person; and
- (s) "trustee" means any person, including the founder of a trust, to whom property is bequeathed in order for such property to be administered for the benefit of another person. ADJUDICATION USING A POINT SYSTEM
- 2.1 The bidder obtaining the highest number of total points will be awarded the contract.
- 2.2 Preference points shall be calculated after prices have been brought to a comparative basis taking into account all factors of non-firm prices and all unconditional discounts.
- 2.3 Points scored must be rounded off to the nearest 2 decimal places.
- 2.4 In the event that two or more bids have scored equal total points, the successful bid must be the one scoring the highest number of preference points for B-BBEE.
- 2.5 However, when functionality is part of the evaluation process and two or more bids have scored equal points

DRAFTED BY:

RECOMMENDED BY

REVIEWED BY:

APPROVED BY BSC CHAIRPERSON

ADVERT APPROVED BY:

SCMU3-19/20-0268-NMA

including equal preference points for B-BBEE, the successful bid must be the one scoring the highest score for functionality.

2.6 Should two or more bids be equal in all respects, the award shall be decided by the drawing of lots.

3. POINTS AWARDED FOR PRICE

3.1 THE 80/20 OR 90/10 PREFERENCE POINT SYSTEMS

A maximum of 80 or 90 points is allocated for price on the following basis:

80/20 or 90/10

or

 $Ps = 90 \left(1 - \frac{Pt - P\min}{P\min} \right)$

Where

Ps = Points scored for comparative price of bid under consideration

Pt

Comparative price of bid under consideration

Pmin

Comparative price of lowest acceptable bid

4. POINTS AWARDED FOR B-BBEE STATUS LEVEL OF CONTRIBUTION

4.1 In terms of Regulation 5 (2) and 6 (2) of the Preferential Procurement Regulations, preference points must be awarded to a bidder for attaining the B-BBEE status level of contribution in accordance with the table below:

B-BBEE Status Level of Contributor	Number of points (90/10 system)	Number of points (80/20 system)
1	10	20
2	9	18
3	8	14
4	5	12
5	4	8
6	3	6
7	2	4
8	1	2
Non-compliant contributor	0	0

- 4.2 A bidder who qualifies as a EME in terms of the B-BBEE Act must submit a sworn affidavit confirming Annual Total Revenue and Level of Black Ownership.
- 4.3 A Bidder other than EME or QSE must submit their original and valid B-BBEE status level verification certificate or a certified copy thereof, substantiating their B-BBEE rating issued by a Registered Auditor approved by IRBA or a Verification Agency accredited by SANAS.
- A trust, consortium or joint venture, will qualify for points for their B-BBEE status level as a legal entity, provided that the entity submits their B-BBEE status level certificate.
- 4.5 A trust, consortium or joint venture will qualify for points for their B-BBEE status level as an unincorporated entity, provided that the entity submits their consolidated B-BBEE scorecard as if they were a group structure

DATE

DATE

DATE

RECOMMENDED BY

REVIEWED BY:

APPROVED BY BSC CHAIRPERSON

ADVERT APPROVED BY:

SCMU3-19/20-0268-NMA

	and that such a consolidated B-BBEE scorecard is prepared for every separate bid.
4.6	Tertiary Institutions and Public Entities will be required to submit their B-BBEE status level certificates in terms of the specialized scorecard contained in the B-BBEE Codes of Good Practice.
4.7	A person will not be awarded points for B-BBEE status level if it is indicated in the bid documents that such a bidder intends sub-contracting more than 25% of the value of the contract to any other enterprise that does not qualify for at least the points that such a bidder qualifies for, unless the intended sub-contractor is an EME that has the capability and ability to execute the sub-contract.
4.8	A person awarded a contract may not sub-contract more than 25% of the value of the contract to any other enterprise that does not have an equal or higher B-BBEE status level than the person concerned, unless the contract is sub-contracted to an EME that has the capability and ability to execute the sub-contract.
5.	BID DECLARATION
5.1	Bidders who claim points in respect of B-BBEE Status Level of Contribution must complete the following:
6.	B-BBEE STATUS LEVEL OF CONTRIBUTION CLAIMED IN TERMS OF PARAGRAPHS 1.4 AND 5.1
6.1	B-BBEE Status Level of Contribution: =(maximum of 10 or 20 points)
	(Points claimed in respect of paragraph 7.1 must be in accordance with the table reflected in paragraph 5.1 and must be substantiated by means of a B-BBEE certificate issued by a Verification Agency accredited by SANAS or a Registered Auditor approved by IRBA or a sworn affidavit.
7.	SUB-CONTRACTING
7.1	Will any portion of the contract be sub-contracted?
	(Tick applicable box)
	YES NO
7.1.1	If yes, indicate:
	i) What percentage of the contract will be subcontracted
(1) 8.	DECLARATION WITH REGARD TO COMPANY/FIRM
8.1	Name of company/firm:
8.2	VAT registration number:
8.3	Company registration number:
8.4	TYPE OF COMPANY/ FIRM
	Partnership/Joint Venture / Consortium One person business/sole propriety Close corporation Company (Pty) Limited
	[TICK APPLICABLE BOX]
8.5	DESCRIBE PRINCIPAL BUSINESS ACTIVITIES
8.5	

SCMU3-19/20-0268-NMA

APPROVED BY BSC CHAIRPERSON

ADVERT APPROVED BY:

REVIEWED BY:

	8.6	CC	MPANY	CLASSIFICATION			
		[<i>Tic</i>	Supp Profe Othe	ufacturer blier essional service provider r service providers, e.g. transporter, etc. ABLE BOX]			
	8.7	Tot	al numbe	er of years the company/firm has been in busines	SS:		
	8.8	I/we	I/we, the undersigned, who is / are duly authorised to do so on behalf of the company/firm, certify that the points claimed, based on the B-BBE status level of contribution indicated in paragraph 7 of the foregoing certificate, qualifies the company/ firm for the preference(s) shown and I / we acknowledge that:				
		i)	The info	ormation furnished is true and correct;			
		ii)	The pre	eference points claimed are in accordance with the form;	e General Conditions as indicated in paragraph 1		
		 In the event of a contract being awarded as a result of points claimed as shown in paragraph 7, contractor may be required to furnish documentary proof to the satisfaction of the purchaser that claims are correct; 					
		iv)	If the B- conditio have –	BBEE status level of contribution has been claimons of contract have not been fulfilled, the purcha	ed or obtained on a fraudulent basis or any of the ser may, in addition to any other remedy it may		
			(a)	disqualify the person from the bidding process;			
			(b)	recover costs, losses or damages it has incurred conduct;	d or suffered as a result of that person's		
		 cancel the contract and claim any damages which it has suffered as a result of having to make less favourable arrangements due to such cancellation; 					
			(d)	restrict the bidder or contractor, its shareholders and directors who acted on a fraudulent basis, f of state for a period not exceeding 10 years, after other side) rule has been applied; and	rom obtaining business from any organ		
			(e)	forward the matter for criminal prosecution			
WI.	TNESSES						
1.					SIGNATURE(S) OF BIDDERS(S)		
2.	•••••			DATE			

1. SIGNATURE(S) OF BIDDERS(S)

DATE:
ADDRESS

RECOMMENDED BY
REVIEWED BY:
APPROVED BY BSC CHAIRPERSON
ADVERT APPROVED BY:
SCMU3-19/20-0268-NMA